

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35; 2 & 3, T20-10

| | | | |
|-------|-------|-------------|-------|
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |
| Alias | _____ | Description | _____ |

GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 215)

Set post 4½ ft. long, 4" sq., 24" in the ground for cor. of secs. 2, 3, 34 and 35, mkd. T19S R10W Sec. 35 on NE.; T20S R10W Sec. 2 on SE.; Sec. 3 on SW.; Sec. 34 on NW. faces, 4 notches on W. and 2 notches on E. edges; from which a

Fir 16" dia., bears N.25°E., 27 lks. dist. mkd. T19S R10W Sec. 35 BT.

Fir 12" dia., bears S.27°E., 73 lks. dist. mkd. T20S R10W Sec. 2 BT.

Fir 10" dia., bears S.37°W., 91 lks. dist. mkd. T20S R10W Sec. 3 BT.

Fir 12" dia., bears N.48°W., 36 lks. dist. mkd. T19S R10W Sec. 34 BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated April 8, 1920 - (DCSO records Vol. 1 Page(s) 262)

"No corners are found between the cor. of secs. 4, 5, 32 and 33, and the cor. which I accept as cor. of Tps. 19 and 20 S., R 10 W., but I find a fairly continuous line of old blazes extending as far as this Tp. cor., but no further eastward."

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11684)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

| | |
|---------------|--|
| T 19 S R 10 W | |
| S 34 S 35 | |
| S 3 S 2 | |
| T 20 S | |
| 1952 | |

from which

A Fir 44" dia., bears N.28½°E., 87 lks. dist. mkd. T19S R10W S35 BT.

A Maple 20" dia., bears S.69¼°E., 109 lks. dist. mkd. T20S R10W S2 BT.

A Fir 10" dia., bears S.48°45'W., 91 lks. dist. mkd. T20S R10W S3 BT.

A Hemlock 12" dia., bears N.84¼°W., 37 lks. dist. mkd. T19S R0W S34 BT.

Fd. OK, June 1982 by W. Shull - M 92-29