

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 282)

The ¼ sec. cor., established on former survey*, which is a Fir post, 3 ft. long, 3" sq., 24" in the ground, mkd: ¼ S34 on W and 35 on E faces; from which
 An Alder, 5" dia., bears N.38°E., 56 lks., mkd: ¼ S BT.
 A Fir, 4" dia., bears S.38°W., 73 lks., mkd: ¼ S BT.
* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

William Shull - For: USFS - June 1982 - M 92-29

Set - USFS monument mkd: T19S R10W ¼ S34 35 1982 PLS 909.
 20" D.Fir, N.65°E., 46.4 ft., scribed "¼ S35 BT"
 16" D.Fir, S.50°W., 11.8 ft., scribed "¼ S34 BT"

Ernesto R. Alvarado, USFS Siuslaw Dist. - Witness: Elwin Price - Sept. 1982 - C.S. 59/30 & C.S. 62/33-1

REFERENCED OUT FOR LOGGING
Found - USFS alum. cap properly mkd. 1982
 23" D.Fir, N.63°E., (to PLS tag) 46.4 ft., scribing visible "¼ S35 BT"
 17" D.Fir, S.49°W., (to PLS tag) 11.8 ft., scribing visible "¼ S34 BT"
Cap removed and stored at Mapleton Ranger Dist.
Reference pts: Bearings & distances are to top of nail head.
 34" D.Fir w/8" X 3/8" nail, bears N.20°30'E. 95.2 ft
 14" D.Fir w/8" x 3/8" nail, bears N.80°30'W. 53.0 ft
 25" D.Fir w/8" X 3/8" nail, bears N.80°E. 35.7 ft.
Location: Go to end of FS Rd. #942, continue along P-line (road to be completed soon) approx. 0.4 mi. Corner is at junction of P-line 2300-0942 and 2300-946 (from south) corner falls on top of ridge. Reference out the corner from the center of the road being built.

Ernesto R. Alvarado, USFS - Don Large - Gene Tracy - Feb. 1986 - C.S. 62/33-2

Found - The 3 reference markers & were not disturbed by the road construction. The 2 BTs set by Wm. Shull were destroyed by the road construction.
 34" D.Fir w/8" X 3/8" nail, bears N.20°30'E. 95.2 ft
(Cont. next page)

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

14" D.Fir w/8" x 3/8" nail, bears N.80°30'W. 53.0 ft.
25" D.Fir w/8" X 3/8" nail, bears N.80°E. 35.7 ft.
Set - At intersections of distance from the 3 reference
markers - Set Douglas Co. brass cap, 10" below
surface of road. Cap mkd: T19S R10W ¼ S 34 35,
1986 USFS alum. cap buried alongside.
New BTs- 38" D.Fir bears N.39°W., 25 ft. to a nail mkd: ¼ S34
CS BT.
26" D.Fir bears S.83 3/4°E., 37.3 ft. to a nail mkd:
¼ S35 CS BT.
Distances are to side & center of trees at root crown.
Location - Go USFS Rd. No. 23 to USFS Rd. No. 942. From gate
go 1 mile to intersection of USFS Rd. #946. The corner is 10"
below road surface on the westside of USFS Rd. #942 at
intersection.