

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 35; & 2, T20-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 215-16)

Set post 4 ft. long, 3½" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on N. face; from which a
Fir 18" dia., bears N.42°E., 67 lks. dist. mkd. ¼ S BT.
Fir 20" dia., bears S.37°W., 73 lks. dist. mkd. ¼ S BT.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated April 8, 1920 - (DCSO records Vol. 1 Page(s) 262)

"No corners are found between the cor. of secs. 4, 5, 32 and 33, and the cor. which I accept as cor. of Tps. 19 and 20 S., R 10 W., but I find a fairly continuous line of old blazes extending as far as this Tp. cor., but no further eastward."

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11685)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd: ¼ $\frac{S\ 35}{S\ 2}$
1952

from which
A Fir 20" dia., bears N.71°E., 10 lks. dist. mkd. ¼ S35 BT.
A Fir 22" dia., bears S.4¼°W., 22 lks. dist. mkd. ¼ S2 BT.