

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 274)

-----  
The ¼ sec. cor., established on former survey\*, which is a Chittem tree, 6 ins. dia., marked ¼ S35 on W and 36 on E sides; from which

A Vine Maple, 6" dia., bears S.25°E., 16 lks., mkd: ¼ S BT

A Fir, 10" dia., bears S.83°W., 16 lks., mkd: ¼ S BT.

This cor. is in the S edge of a Vine Maple bottom, bears E & W.

\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

James W. Prochnau - For: US Forest Service - July 29, 1971 - C.S. File 55/206-4 - M 43-22

-----  
No evidence found of the orig. corner. At the properly proportioned dist., I placed 2"x36" galv. iron pipe, flanged at the bottom & capped with a bronze disk welded on the top. The monument projects 6" above the ground, I filled in around the pipe monument with stone & packed earth. I stamped the disk:

¼ S35|S36  
1971  
4185

I established new BTs as follows. Each BT has a scribed face & a USFS BT sign breast high & facing the monument:

- A 20" D.Fir bears N.54°W., 27.5 ft.
- A 46" D.Fir bears S.39°E., 12.0 ft.