

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705 dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 276)

The cor. of secs. 23, 24, 25, & 26, established on former survey*, which is Chittem post, 3 ft. long, 4" sq., 24" in the ground, T19S S24 on NE, R10W S25 on SE, S26 on SW and S23 on NW faces, w/2 notches on S & 1 notch on E edges; from which

- A Chittem, 5" dia., bears N.11°E., 26 lks., mkd: T19S R10W S24 BT.
- A Fir, 6" dia., bears S.17°E., 20 lks., mkd: T19S R10W S25 BT.
- A Fir, 8" dia., bears S.30°W., 17 lks., mkd: T19S R10W S26 BT.
- A Fir, 6" dia., bears N.70°W., 40 lks., mkd: T19S R10W S23 BT.

* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM dependent resurvey by Robert W. Dahl, Cadastral Surveyor, under Group #1450, surveyed Aug. 1988/Oct. 1989 - (DCSO records Vol. 49 Page(s) 18772)

Point for cor. of secs. 23, 24, 25, & 26, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 23" in the ground, with brass cap marked:

T19S R10W
S 23 S 24
S 26 S 25
1989

from which

- A Fir, 93" dia., bears N.55°E., 34 lks., mkd: T19S R10W S24 BT.
- A Hemlock, 17" dia., bears S.75°E., 26 lks., mkd: T19S R10W S25 BT.
- A Cedar, 10" dia., bears S.53°W., 30½ lks., mkd: T19S R10W S26 BT.
- A Fir, 21" dia., bears N.71 3/4°W., 44 lks., mkd: T19S R10W S23 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.