

PRIMARY CORNER DESCRIPTION SE. Cor. for Sec. 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 212)

Set post 4 ft. long, 4" sq., 24" in the ground for cor. of Tps. 19 and 20 S., Rs. 9 and 10 W., marked T19S R9W Sec. 31 on NE.; R9W Sec. 6 on SE.; T20S R10W Sec. 1 on SW.; R10W Sec. 36 on NW. faces, with 6 notches on S., E., and W. faces; from which a

- Fir 12" dia., bears N.20°E., 56 lks. dist. mkd. T19S R9W Sec.31 BT.
- Fir 10" dia., bears N.34°W., 76 lks. dist. mkd. T19S R10W Sec. 36 BT.
- Hemlock 8" dia., bears S.63°W., 80 lks. dist., mkd. T20S R10W sec. 1 BT.
- Hemlock 14" dia., bears S.21°E., 91 lks. dist. mkd. T20S R9W Sec. 6 BT.

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated April 8, 1920 - (DCSO records Vol. 1 Page(s) 263)

At a point which I ultimately accept as the cor. to Tps. 19 and 20 S., R 10 W., where I find evidences of a cor., though not in agreement with the description given in the field notes of the Martin survey. At this point, I find three old and decayed Fir stubs, one plainly marked, and the other two apparently showing indications of having been marked, but so badly defaced by fire that certain identification is difficult. This is very evidently the cor. accepted by Chandler in his survey. The range line running N. from this point is fairly well marked, but no evidence of survey is found further South. The point appears to be locally recognized as the Tp. cor. and I so accept it and re-establish the cor., as follows:

No monument or definite point is found. The three stubs, above mentioned, are close together and indicate a point at which I

Set a sandstone 20x12x6 ins., 12" in the ground for cor. of Tps. 19 and 20 S., R.10W., marked 19S on N.; 20S on S.; 10W on W.; with 6 grooves on N., S., and W. faces; from which

- An Alder 18" dia., bears S.45°W., 21 lks. dist. mkd. T20S R10W S1 BT.
- A Chinquapin 20" dia., bears N.52°W., 23 lks. dist., mkd. T19S R10W S36 BT.

No iron post available for this corner.

- A Fir stub 24" dia., 10 ft. high, bears S.49°E., 15 lks. dist., badly defced by fire, showing indications of scribe marks on the bark. (Cont. Next Page)

PRIMARY CORNER DESCRIPTION SE. Cor. for Sec. 36

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A Fir stub 24" dia., 3 ft. high, bears S.20°W., 5 lks. dist., plainly scribed on the bark, R10W S1 BT.
A Fir stub 36" dia., 6 ft. high, bears N.80°W., 11 lks. dist., badly defaced by fire, showing evidence of old blaze on the bark.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11681)

The cor. of Tps. 19 and 20 S., R10W., monumented with a crumbling sandstone, 12x10x4 ins., set 6" in the ground, mkd. with 6 grooves on S. and W. faces, the other marks gone, from which

An Alder 18" dia., bears S.43°W., 21 lks. dist., with partial scribe marks. (Rec. brg. S.45°W.)
A dead Chinquapin 18" dia., bears N.52°W., 23 lks. dist., with blaze healed.

At the corner point
Set an iron post, 3 ft. long, 3" dia., 28" in the ground, with brass cap mkd:

T 19 S
R 10 W T 20 S
S 36 R 9 W
S 1 S 6
T 20 S
1952

from which new bearing trees:
A Fir 30" dia., bears S.14°W., 47 lks. dist. mkd. T20S R10W S1 BT.
A Chinquapin 18" dia., bears N.38½°W., 31 lks. dist. mkd. T19S R10W S36 BT.
Reset the sandstone alongside the iron post.