

PRIMARY CORNER DESCRIPTION SW. Cor. for Sec. 31, T19-9

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 14, 1899 - (DCSO records Vol. 44 Page(s) 17052)

-----  
(At point 9.29 chs. N. of Tsp. 19 and 20S, R10W)  
A Chittem, 6" dia., for closing cor. of Tps. 19 & 20 S., R 9 W. I marked C.C. R9W on E.; T20S Sec. 6 on S.; and T19S Sec. 31 on N. sides with 6 notches on NE. and S. sides, from which  
A Fir 20" dia., bears S.26 3/4°E., 26 lks. dist. mkd. T20S R9W S6 BT.  
A Chittem 6" dia., bears N.20°E., 40 lks. dist. mkd. T19S R9W S31 BT.

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 19, 1899 - (DCSO records Vol. 1 Page(s) 269)

-----  
On top of spur, 75 ft. above ravine, bears W. The old closing cor. of Tps. 19 & 20 S., R 9 W.; I destroy this cor. \* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated April 8, 1920 - (DCSO records Vol. 1 Page(s) 265)

-----  
At the Tsp. cor., which is a Chittem, 6" dia., marked and witnessed as described by the Surveyor General, except that the SE. bearing tree is dead. I take new bearing tree.  
From the corner,  
(Old bearing tree), a Chittem 6" dia., bears N.20°E., 40 lks. dist. mkd. T19S R9W S31 BT.  
(New Bearing tree, a Chittem 4" dia., bears S.38°E., 10 lks. dist. mkd. T20S R9W S6 CC BT.

Survey by Forest J. Hales - For: International Paper Co. - June 3, 1978 - M 71-62

-----  
Found - Remains of the 6" Chittem.  
Set 5/8" x 40" Iron rod S.20°W., 40 lks. from the uproot hole where the 6" Chittem stood.  
New BTs- 48" D.Fir bears N.32½°E., 49.0 ft. mkd. "BT S31 T19S R9W."  
44" Fir bears S.53½°E., 18.2 ft. mkd. "BT S6 T20S R9W."

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - L.E. Monrean; R. Smith; S. Flause, crew - Jan. 5, 1984 - C.S. File 62/16

CORNER REPORT ONLY

History- This corner was originally established in 1899 by Chandler. The cor. mon. was a 6" Chittum - BTs were: 6" Chittum, N.20°E., 40 lks. and 20" Fir S.26 3/4°E., 26 lks.

In 1921, Mensch found the cor. & scribed a 4" Chittum, S.38°E., 10 lks., as the orig. Fir BT was dead.

In 1978, Forrest Hales found an uprooted Chittum & set a 5/8" Iron rod for the closing corner monument, holding the position of the found Chittum as the orig. NE. BT.

Found - 5/8" Iron rod set by Hales.

48" D.Fir, single blazed with scribing, bears N.32½°E., 51.1 ft. (Rec. 49.0 ft. (Hales BT)

40" D.Fir (Rec. 44") single blazed with visible scribing "S6 T20S R9W BT" bears S.50°E., 21.4 ft. (Rec. S.53½°E., 18.2 ft.)

I visited this corner with Ernesto Alvarado of the Siuslaw National Forest, who produced a copy (see file) of a Forest Service "CORNER RECORD" card dated 1968. According to the info. on the card, the cor. had been visited by J. Deaton & D. Thrall 10 years prior to the Hales survey. The card shows that a 16" Fir stub with scribing was located & that blazed lines ran E. & S. from the cor. position. This evidently was accepted as the orig. Fir BT reported by Mensch to be dead in 1921 (47 years earlier). Mr. Alvarado indicated that he had set a temporary stake at the orig. brg. & dst. from a decayed Fir stump (stump bears S.26 3/4°E., 26 lks. from stake)

From the Hales 5/8" I.R., we measure to the temp. stake set by Alvarado, N.22°E., 16.9 ft. & we measure to the 30" Fir stump, S.89½°E., 11.3 ft. We did not find any scribing on the Fir stump. We found blazed line running E. & N. from the general area of the closing cor. (the blazed line to the N. was E. of the line mkd. by Hales.)

Without performing a survey, it would not be practical to distinguish if an intersection point could be determined from the found blazed lines.

Bearing tree tags with no infor., (name, date, brgs. or dists.) scribed were found. One tag was found on the 48" Hales BT and faced a South-Southwest direction. The other was found on a Maple stump (approx. 8 ft. easterly of Hales monument) and faced North-Northwest.

This is a report only. No monuments or BTs were set or scribed. (Cont. Next Page)

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 700109

PRIMARY CORNER DESCRIPTION SW. Cor. for Sec. 31, T19-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

No orig. evidence of the corner mon. or its accessories could be ascertained at this time.  
(Sketch in file and additional documentation.)