

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 19, 1899 - (DCSO records Vol. 1 Page(s) 269)

-----  
The ¼ sec. cor., established on former survey\*, which is a Cherry tree, 8" dia., mkd. ¼ S 36 on W. side; from which  
A Cherry tree, 12" dia., bears S.72°E., 35 lks. dist. mkd. ¼ S BT.  
A Cherry 9" dia., bears S.10°W., 10 lks. dist. mkd. ¼ S BT.

(\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.)

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated April 8, 1920 - (DCSO records Vol. 1 Page(s) 264)

-----  
The ¼ sec. cor. on E. bdy. of sec.36, originally a Cherry 8" dia., is now dead, decayed and fallen. Both bearing trees also dead and down; marks legible on cor. and bearing trees. At exact cor. point, in cavity of decayed cor. tree, Set a sandstone 20x10x6 ins., 12" in the ground for ¼ sec.cor. of sec. 36 only, marked ¼ on W. side; from which (new bearing trees)  
A Cedar 28" dia., S.3°W., 153 lks. dist. mkd. ¼ S36 BT.  
A Chittem 12" dia., N.30°W., 95 lks. dist. mkd. ¼ S36 BT.  
No iron posts available for this corner.

Survey by Forrest J. Hales - For: International Paper Co. - June 3, 1978 - M 71-62

-----  
Found no evidence of the 1920 Govt. survey corner.  
At proportional distance:  
Set 5/8" x 40" Iron rod, from which  
40" Red Cedar bears S.7°W., 87.2 ft. mkd. "BT ¼ S36 T19S R10W.  
28" Red Cedar S.42½°W., 58.8 ft. mkd. "BT ¼ S36 T19S R10W.

Survey by Forrest J. Hales, PLS #453 - For: Forrest Hales - March 30, 1984 - M 96-35

-----  
Set 5/8" x 40" Iron rod mkd. "F.J.H. 453, from which  
40" Red Cedar stump bears S.9°55'W., 93.8 ft. to face.  
28" Red Cedar stump bears S.42°36'W., 66.9 ft. to face.  
Found BTs recorded by Hales in 1978. 1978 monument was removed by logging.

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ernesto Alvarado, U.S.F.S., deputized by DCSO -Wit: Carol Dickinson; Paul Smith - June 25, 1984 - C.S. File 62/15

Found - Sandstone, 1.8 ft. x 1.0 ft. x 0.6 ft. with "X" chiseled on top.

Hales 5/8" re-bar, (1984) bears S.59½°E., 13.49 ft. from original stone.

Original BT, 42" Cedar stump bears S.3°W., 100.4 ft. Found reverse orig. scribing. Stump was rescribed by Hales "BT ¼ S36"

31" Cedar stump (Hales) bears S.32°W., 66.2 ft. open face, scribing visible "BT ¼ S36"

Set County brass cap at exact position of the original stone, marked "Douglas County Surveyors Office T19S R10W S36 1/4 R9W 1984". Original stone placed alongside cap. Cap surrounded with stones.

New Accessories:

3/8" Rebars driven into tops of both BT stumps.

Attention and property boundary signs on metal fence posts placed on line North and South of corner ± 4 ft. (Distances are to top of stumps at rebar)

Location: From Rd. #48, go 2.8 miles up Rd. #23 to gravel road running S'ly (in Sec. 35, clearcut). Drive up road 1.7 miles to where it forks near E. side of clearcut. Go down N'ly fork to landing at end. From N. end of landing, cor. lies E'ly 450 ft. in craw near cutting line.