

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 19, 1899 - (DCSO records Vol. 1 Page(s) 270)

Set a basalt stone 12x10x8 ins., 9" in the ground, for ¼ sec. cor. mkd. ¼ on W. face; from which

An Alder 4" dia., bears N.10°W., 12 lks. dist. mkd. ¼ S25 BT.

An Alder 4" dia., bears S.19°W., 5 lks. dist. mkd. ¼ S25 BT.

From this cor., the old ¼ sec. cor. brs. E., 4 lks. below top of spur, course SW.

(* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.)

BLM survey by Thomas A. Tillman; Robert L. Holm & Floyd A. Brooks, Cadastral Surveyors, under Group #307, surveyed May 1957/Sept. 1958 - (DCSO records Vol. 31 Page(s) 13030)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd:

¼
T 19 S
S 25
R 10 W
1958

from which

A Cedar 13" dia., bears N.34½°W., 28 lks. mkd. ¼ S25 BT.

A Fir 21" dia., bears S.11°W., 16 lks. mkd. ¼ S25 BT.

Fd. OK and used in BLM survey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 - (DCSO records Vol. 37 Page(s) 15426-27)

BLM Resurvey by Robert W. Dahl, Cadastral Surveyor, under Group #1450, surveyed Aug. 1988/May 1991 - (DCSO records Vol. 49 Page(s) 18752-53)

The ¼ sec. cor. of sec. 25 only, determined from the bearing trees; the corner point falls in a small slide, the monument has been disturbed and was found down the hill, from which the bearing trees mkd. by Tillman, etal:

(Cont. Next Page)

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 27" dia., bears S.11°W., 16 lks. dist. with healed blaze.

A Cedar 20" dia., bears N.34½°W., 27 lks. dist. with healed blaze. (Rec. 28 lks.)

At the corner point

RESET the iron post 28" long, 2½" dia., on bedrock, over a mark < chiseled in the bedrock, and in a mound of stone, 6 ft. base to top.