

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 700251

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 30 only, T19-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM survey by Thomas A. Tillman; Robert L. Holm & Floyd A. Brooks, Cadastral Surveyors, under Group #307, surveyed May 1957/Sept. 1958 - (DCSO records Vol. 31 Page(s) 13030-31)

Point for the ¼ sec. cor. of sec. 30 only, on the W. bdy. of T19S R9W, at midpoint between closing corners.

Set an iron post 28" long, 2½" dia., 22" in the ground, with brass cap mkd: ¼

T 19 S
S 30
R 9 W
1958

from which

An Alder 18" dia., bears N.7°E., 55 lks. dist. mkd. ¼ S30 BT.

An Alder 23" dia., bears S.78°E., 43 lks. dist. mkd. ¼ S30 BT.

Fd. OK and used in BLM survey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 - (DCSO records Vol. 37 Page(s) 15427)

BLM Resurvey by Robert W. Dahl, Cadastral Surveyor, under Group #1450, surveyed Aug. 1988/May 1991 - (DCSO records Vol. 49 Page(s) 18753)

The ¼ sec. cor. of sec. 30 only, T19S R9W., erroneously established by Tillman, etal, in 1957-58, bears West, 0.215 chs. dist., monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, mkd. and witnessed as described in the official record. **Remove the iron post and obliterate the scribe marks on the bearing trees.**