

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only, (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 19, 1899 - (DCSO records Vol. 1 Page(s) 270-71)

The cor. of secs. 24 and 25, established on former survey*, which is a post, 3 ft. long, 4" sq., 24" in the ground, mkd. T19S S25 on SW. and R10W S24 on NW. faces, with 2 notches on S. and 4 notches on N. edges; from which

An Alder 8" dia., bears S.25°W., 16 lks. dist. mkd. T19S R10W S25 BT.

An Alder 7" dia., bears N.34°W., 20 lks. dist. mkd. T19S R10W S24 BT.

* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM survey by Thomas A. Tillman; Robert L. Holm & Floyd A. Brooks, Cadastral Surveyors, under Group #307, surveyed May 1957/Sept. 1958 - (DCSO records Vol. 31 Page(s) 13031)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd:

T 19 S T 19 S
 S 24
 S 25 S 30
R 10 W R 9 W
 1958

from which

A Cedar 60" dia., bears S.25°W., 47 lks. dist. mkd. T19S R10W S25 BT.

A Cedar 30" dia., bears N.40°W., 68 lks. dist. mkd. T19S R10W S24 BT.

Cor. Fd. OK and used in BLM survey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 - (DCSO records Vol. 37 Page(s) 15427)

BLM Resurvey by Robert W. Dahl, Cadastral Surveyor, under Group #1450, surveyed Aug. 1988/May 1991 - (DCSO records Vol. 49 Page(s) 18753)

The cor. of secs. 24 & 25 only, monumented with an iron post 2½" dia., firmly set, projecting 8" above ground, with brass cap mkd. in 1958, from which the bearing trees mkd. by Tillman, Holm & Brooks:
(Cont. Next Page)

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only, (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Cedar 72" dia., bears S.36°W., 45 lks. dist., with scribe marks T19S R10W S24 BT visible on partially healed blaze. (Rec. S.25°W., 47 lks.)
A Cedar 39" dia., bears N.29°W., 68 lks. dist. with scribe marks T19S R10W S25 BT visible on partially healed blaze. (Rec. N.40°W.)