

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 19, 1899 - (DCSO records Vol. 1 Page(s) 271)

-----  
Set an Alder post 3 ft. long, 4' sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S24 on W. face; from which  
    An Alder 4" dia., bears N.18°W., 15 lks. dist. mkd. ¼ S BT  
    An Alder 7" dia., bears S.19°W., 17 lks. dist. mkd. ¼ S BT  
From this cor., the old ¼ sec. cor. bears E. 4 lks. dist. I destroy it.  
\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM survey by Thomas A. Tillman; Robert L. Holm & Floyd A. Brooks, Cadastral Surveyors, under Group #307, surveyed May 1957/Sept. 1958 - (DCSO records Vol. 31 Page(s) 13032)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd:  
    ¼  
    T 19 S  
    S 24  
    R 10 W  
    1958

from which  
    A Hemlock 25" dia., bears N.49°W., 96 lks. dist. mkd. ¼ S24 BT.  
    An Alder 22" dia., bears S.7½°W., 105 lks. dist. mkd. ¼ S24 BT.

Cor. Fd. OK and used in BLM survey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 - (DCSO records Vol. 37 Page(s) 15428-29)

BLM Resurvey by Robert W. Dahl, Cadastral Surveyor, under Group #1450, surveyed Aug. 1988/Oct. 1989 - (DCSO records Vol. 49 Page(s) 18767-68)

-----  
The ¼ sec. cor. of sec. 24 only, determined from the remaining bearing tree mkd. by Tillman, etal  
    A Hemlock 43" dia., bears N.49°W., 96 lks. dist., with healed blaze.  
At the corner point  
(Cont. Next Page)

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set a stainless steel post 28" long, 2½" dia., 16" in the ground, over a metal fence post, 6 ft. long, driven 5 ft. into the river bed, and in a mound of stone, 5 ft. base, to top, with brass cap mkd. T19S

R19W R9W

¼

S 24

1989

from which a new bearing tree

A Fir 42" dia., bears S.71°W., 223 lks. dist. mkd. ¼ S24  
BT.

Corner is located in the bed of North Fork Smith River, 80 lks. wide, course S.40°W., 10 lks. W. of the left bank.