

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 700411

PRIMARY CORNER DESCRIPTION C C for Secs. 18 & 19 only, T19-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 414)

-----  
At point of intersection (9.30 chs. N. of the cor. secs. 13 & 24)

Set a basalt stone 16x8x6 ins., 12" in the ground, for closing cor. of secs. 18 & 19, marked CC on E. face, with 3 grooves on N. and S. faces; from which

A Fir 14" dia., bears N.15°E., 26 lks. dist. mkd. T19S R9W S18 BT.

A Fir 6" dia., bears S.29°E., 20 lks. dist. mkd. T19S R9W S19 BT.

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 19, 1899 - (DCSO records Vol. 1 Page(s) 272)

-----  
The old closing cor. of secs. 18 & 19, I destroy it.

\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM survey by Thomas A. Tillman; Robert L. Holm & Floyd A. Brooks, Cadastral Surveyors, under Group #307, surveyed May 1957/Sept. 1958 - (DCSO records Vol. 31 Page(s) 13033-34)

-----  
Point for the closing sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd:

T 19 S T 19 S  
S 13  $\frac{S 18}{S 19}$  CC  
R 10 W R 9 W  
1958

from which

A Fir 58" dia., bears N.82°E., 63 lks. dist. mkd. T19S R9W S18 CC BT.

A Fir 43" dia., bears S.6°E., 62 lks. dist. mkd. T19S R9W S19 CC BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION C C for Secs. 18 & 19 only, T19-9

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM survey by Donald R. Beck & Peter A. Peterson, Cadastral Surveyors, under Group #307, surveyed April 1968/Aug. 1976 - (DCSO records Vol. 37 Page(s) 15430)

-----  
The closing cor., monumented with an iron post 2½" dia., firmly set, projecting 6" above ground, with brass cap mkd. in 1958,  
from which the remains of the bearing trees mkd. by Tillman, etal:

A root hole bears N.82°E., 63 lks. dist., with a down Fir alongside 60" dia., with healed blaze.

A sawed Fir stump 44" dia., bears S.6°E., 62 lks. dist. with scribe marks BT visible on open blaze.

and a bearing tree of no record:

A Fir 47" dia., bears N.14°E., 60 lks. dist., with healed blaze.

and a new bearing tree:

A Cedar 14" dia., bears S.28°E., 141 lks. dist. mkd. T19S R9W S19 CC BT.

BLM Resurvey by Robert W. Dahl, Cadastral Surveyor, under Group #1450, surveyed Aug. 1988/Oct. 1989 - (DCSO records Vol. 49 Page(s) 18769)

-----  
The closing cor., monumented with an iron post 2½" dia., firmly set, projecting 2" above ground, with brass cap mkd. in 1958,

from which the remains of bearing trees mkd. by Tillman, etal

A root hole bears N.82°E., 63 lks. dist.

A Fir stump 44" dia., bears S.6°E., 62 lks. dist., no marks visible.

and the remains of a bearing tree reported by Beck & Peterson

A Fir stump 47" dia., bears N.7½°E., 60 ks. dist., with healed blaze. (Rec. N.14°E.)

and the remains of a bearing tree mkd. by Beck & Peterson:

A Cedar stump 18" dia., 8 ft. high, bears S.28°E., 141 lks. dist., with scribe mrks T19S R10W S19 CC BT visible on partially healed blaze.

and new accessories:

A Fir 4" dia., bears N.59¼°E., 58½ lks. dist., mkd. X BT.

A stainless steel post, 28" long, 2½" dia., set 28" in the ground, for a reference monument, bears S.2°36'W., 75.5 lks. dist., with brass cap mkd. RM T19S R9W S19 CC 49.8 FT TO COR 1989 and an arrow pointing to the corner.

Corner is located on a spur, slopes E.

Fd. OK, June 1991 by R. Ward - M 113-37 A & B

