

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 700509

PRIMARY CORNER DESCRIPTION C C for Secs. 7 & 18 only, T19-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 415-16)

At point of intersection (9.40 chs. N. of the cor. of secs. 12 & 13)

Set a sandstone 18x18x6 ins., 15" in the ground for closing cor. of secs. 7 and 18 marked CC on E. face, with 4 grooves on S. and 2 grooves on N. faces; from which

A Fir 7" dia., bears N.22°E., 39 lks. dist. mkd. T19S R9W S7 BT.

A Fir 7" dia., bears S.20°E., 40 lks. dist. mkd. T19S R9W S18 BT.

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 19, 1899 - (DCSO records Vol. 1 Page(s) 272)

The old closing cor. of secs. 7 and 18; I destroy it.

* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM survey by Thomas A. Tillman; Robert L. Holm & Floyd A. Brooks, Cadastral Surveyors, under Group #307, surveyed May 1957/Sept. 1958 - (DCSO records Vol. 31 Page(s) 13063)

(78.90 chs.)

The Chandler closing corner of secs. 7 & 18, monumented with a sandstone, 18x18x6 ins., firmly set 8" in the ground, mkd. CC on the E. face, with 4 grooves on the S. and 2 grooves on the N. faces, from which the original bearing trees:

A Fir 20" dia., bears N.17¼°E., 34 lks. dist., with healed blaze. (Rec. N.22°E., 39 lks. dist.)

A Fir 28" dia., bears S.16°E., 48 lks. dist., with fragmentary scribe marks visible on opened blaze. (Rec. S.20°E., 40 lks. dist.)

(78.95 chs.)

Point for the closing cor. of secs. 7 and 18.

Set an iron post 28" long, 2½" dia., 22" in the ground, with brass cap mkd. T 19 S

S 12 $\frac{S 7}{S 18}$ CC
R 10 W R 9 W
1958

from which

(Cont. next page)

PRIMARY CORNER DESCRIPTION C C for Secs. 7 & 18 only, T19-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 24" dia., bears N.12°E., 88 lks. dist. mkd. T19S R9W S7 CC BT.
 A Hemlock 13" dia., bears S.63¼°E., 60 lks. dist. mkd. T19S R9W S18 CC BT.

Fd. OK, Sept. 1988 by D. Baker - M 107-1


BLM Resurvey by Robert W. Dahl, Cadastral Surveyor, under Group #1450, surveyed Aug. 1988/May 1991 - (DCSO records Vol. 49 Page(s) 18761)

 (39.430 chs.) The orig. closing cor. of secs. 7 and 18, monumented with a sandstone, 18x18x6 ins., in two pieces, loosely sset 2" in the ground mkd. CC on the E. face, with 4 grooves on the S. and 2 grooves on the N. faces, from which the original bearing trees:

- A Fir stump 30" dia., bears N.19°E., 36 lks. dist. with healed blaze. (Rec. N.17 3/4°E., 34 lks.)
- A Fir 40" dia., bears S.19¼°E., 45 lks. dist. with healed blaze. (Rec. S.16°E., 48 lks.)

Reset stone in place, flush with the ground surface.

(39.440 chs.) True point for the closing cor. of secs. 7 & 18. From this point, the closing cor. of secs. 7 and 18 established by Tillman, etal in 1957-58, bears N.88°50'00"W., 0.040 chs. dist., monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap mkd. and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1989 1958, reset the monument flush with the ground surface, obliterated the scribe marks on the NE. BT and at the true corner point. Set a stainless steel post 28" long, 2½" dia., 23" in the ground with brass cap mkd. T19S



from which
 A stainless steel post 18" long, 2½" dia., set 28" in the ground, for a reference monument, bears S.87°19'E., 82.3 lks. dist., with brass cap mkd. RM T19S R9W S18 54.3 FT TO COR 1989 and an arrow pointing to the corner.

and a bearing tree mkd. by Tillman, etal
 A Hemlock 15" dia., bears S.62¼°E., 54 lks. dist. with healed blaze.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.
 (From this same point, the cor. of secs. 12 & 13 only, T19S R10W., bears S.1°15'00"W., 8.945 chs.)