

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 700609

PRIMARY CORNER DESCRIPTION C C for Secs. 6 & 7 only, T19-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 417-18)

-----  
At point of intersection (9.50 chs. N. of the cor. of 1 & 12)  
Set a sandstone 16x12x6 ins., 12" in the ground for closing cor. of secs. 6 & 7, marked CC on E. face, with 5 notches on S. and 1 notch on N. edges; from which  
A Fir 40" dia., bears N.56°E., 260 lks. dist. mkd. T19S R9W S6 BT.  
A dead Fir 16" dia., bears S.78°E., 14 lks. dist. mkd. T19S R9W S7 BT.

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 19, 1899 - (DCSO records Vol. 1 Page(s) 273)

-----  
The old closing cor. of secs. 6 & 7, T19S R9W.; I also destroy it.  
\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM survey by Thomas A. Tillman; Robert L. Holm & Floyd A. Brooks, Cadastral Surveyors, under Group #307, surveyed May 1957/Sept. 1958 - (DCSO records Vol. 31 Page(s) 13066-67)

-----  
(39.31 chs.) The Chandler closing corner of secs. 6 & 7, monumented with a sandstone 16x12x6 ins., mkd. CC on E. face, with 5 notches on the S. and 1 notch on N. edges; from which an original bearing tree:  
A Fir snag 40" dia., bears N.56°E., 260 lks. dist., with healed blaze.  
There is no evidence of other bearing tree.  
(39.37 chs.) (N.89°16'W.) Intersect the E. bdy. of sec. 1, T19S R10W  
Point for the closing corner of secs. 6 & 7.  
Set an iron post 28" long, 2½" dia., 22" in the ground with brass cap mkd:  
T 19 S  
S 1  $\frac{S}{S}$   $\frac{6}{7}$  CC  
R 10 W R 9 W  
1958 from which  
A Fir 15" dia., bears N.56°E., 118 lks. dist. mkd. T19S R9W S6 CC BT.  
A Fir 10" dia., bears S.88½°E., 99 lks. dist. mkd. T19S R9W S7 CC BT.

PRIMARY CORNER DESCRIPTION C C for Secs. 6 & 7 only, T19-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Clyde Mulkins, LS #2006 - For: U.S. Forest Service - March 18, 1983 - M 94-21 A, B, & C.

-----

Found - BLM brass cap/iron pipe mkd. in 1958.  
 15" D.Fir bears N.56°E., 71.6 ft. with healed face,  
 18" D.Fir bears S.53°E., 76.1 ft. with visible scribe.  
 16" D.Fir bears S.10°W., 75.4 ft. with visible scribe.  
 13" D.Fir bears N.51°W., 2.3 ft. with healed blaze.

Fd. OK, Sept. 1988 by D. Baker - M 107-1

BLM Resurvey by Robert W. Dahl, Cadastral Surveyor, under Group #1450, surveyed Aug. 1988/May 1991 - (DCSO records Vol. 49 Page(s) 18762-63)

-----

(39.310 chs.)  
 The original closing cor. of secs. 6 & 7, monumented with a sandstone 16x12x6 ins., crumbling into pieces, firmly set flush with ground surface, mkd. CC on E. face and other indistinct marks, from which the remaining original bearing trees:  
 A Fir snag stump 40" dia., bears N.56½°E., 253 lks. dist., no marks visible. (Rec. N.56°E., 260 lks.)

(39.325 chs.) (N.89°09'30"W.)  
 True point for the closing cor. of secs. 6 & 7.  
 From this point, the closing cor. established by Tillman, etal, in 1957-58, bears N.89°09'30"W., 0.045 chs. dist., monumented with an iron post 2½" dia., firmly set, projecting 8" above ground, with brass cap mkd. and witnessed as described in the official record, except no evidence of the SE. bearing tree remains. Amended the marks on the brass cap to read AM 1989 1957, Reset the monument flush with the ground surface, obliterated the scribe marks on the remaining bearing tree and at the true corner point.  
 Set a stainless steel post 28" long, 2½" dia., 23" in the ground with brass cap mkd: T19S

R10W      R9W  
 S 1  $\frac{S 6}{S 7}$  CC  
 1989

from which

A stainless steel post 28" long, 2½" dia., set 28" in the ground, for a reference monument bears S.88°5'E., 167.4 lks. dist. with brass cap mkd. RM T19S R9W S7 CC 110.5 FT TO COR 1989 and an arrow pointing to the corner.

(Cont. Next Page)

TOWNSHIP 19 RANGE 10 POINT IDENTIFIER # 700609

PRIMARY CORNER DESCRIPTION C C for Secs. 6 & 7 only, T19-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and a bearing tree mkd. by Alan D. Reid, U.S. Forest Service Forester, in 1958, record held at Mapleton Ranger Station:

A Fir 17" dia., bears N.72½°W., 7½ lks. dist. with healed blaze.

and bearing trees of no known record:

A Fir 25" dia., bears S.51½°E., 111 lks. dist. with healed blaze and a U.S. Plywood tag dated 1975.

A Fir 20" dia., bears S.12¼°W., 115 lks. dist., with healed blaze and a U.S. Plywood tag dated 1975.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.