

PRIMARY CORNER DESCRIPTION W. 1/4 cor. for Sec. 31 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by J. H. McClung, under Contract #173, dated July 20, 1872 - (DCSO records Vol. 2 Page(s) 547)

Set ¼ sec. post, from which
A Fir 14" dia., bears N.55°E., 20 lks.
A Fir 12" dia., bears N.61°W., 22 lks.

GLO Resurvey by Thos. Todd, Contract #574, dated May 19, 1891 (DCSO records Vol. 2 Page(s) 582)

Old ¼ sec. cor. to sec. 31, R6W, which is a post, 3" sq., firmly set in the ground mkd. ¼ S on W. face; from which
A Fir 14" dia., bears N.55°E., 20 lks. dist. mkd. ¼ S BT.
A Fir 12" dia., bears N.61°W., 22 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; C Putnam, crew - Jan. 1962 - C.S. File 49/89-21

Found - Fir tree, now 33", N.55°E., 13.2 ft., chopped open and found good scribing "4 C". Ring count shows scribing to be about 90 years old. This proves it to be McClung's corner set in 1872. Tree in good condition.

No trace found of NW. bearing tree.

Set Iron pipe with brass cap mkd: County Surveyors Office
T20S R6W ¼ | S31
1962

New BT - 20" Fir S.50°E., 35.5 ft. mkd. "¼ S31 CS BT"

Harvey Christensen, survey for Seneca Jones Timber Co. Sept. 1998 - M130-35

Found - D.C.S.O. 2½" Brass cap 1.1 ft. above ground.
BT's - 20" D.Fir, S.50°E., 35.5 ft. stump w/tin cap, old blaze visible.
33" D.Fir, N.55°E., 13.2 ft. stump w/tin cap, w/"4C" visible facing south.

New Accessories -

5" D.Fir, N.73°W., 30.6 ft. blazed & scribed "X BT"

8" D.Fir, S.14°W., 21.5 ft. blazed & scribed "X BT"

8" D.Fir, N.34°E., 23.2 ft. blazed & scribed "¼ S31 BT"

9" D.Fir, S.15°E., 28.8 ft. blazed & scribed "¼ S31 BT"

Note - Set 5 ft. steel post 1 ft. north.