

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25, T20-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 583)

-----  
Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 24 and 25, mkd. T20S R7W on W.; S24 on N.; S25 on S. faces, with 2 notches on S. and 4 notches on N. faces, from which

- A Fir 20" dia., bears N.80°E., 72 lks. dist. mkd. T20S R7W S24 & 25 BT.
- A Fir 20" dia., bears S.5°W., 208 lks. dist. mkd. T20S R7W S25 BT.
- A Maple 6" dia., bears N.43°W., 67 lks. dist. mkd. T20S R7W S24 BT.

-----  
Wilford N Haines (Found & recorded by Milo Godfrey, Feb. 1962 - C.S. File 49/89-28 (Also Haines F.B. H-3 & Map M 21-72)

-----  
Found - Haines' "T" Iron at corner.  
66" Fir, S.5°W., 137.3 ft., shows old scars.  
Old Fir snag, badly decayed, N.82°E. (Notes call for N.80°E.) 47 ft., too far gone to find any scribing.  
48" Fir, N.47°W., 47.8 ft., bark scribed "T20S R7W S24 BT 363" and Haines' metal disc.  
No trace of Maple BT. Notes call for 6" Maple, N.43°W., 44.2 ft.  
This cor. bears South, 209.5 ft. from CC Secs. 19 & 30, T20-6. Todd's field notes call for this cor. to be South, 255.4 ft. from CC.

-----  
Fd. T Iron and 3 BTs, June 1991 by D. Peel - M 113-45

-----  
Rob Ward - For: Roseburg Resources Co. & Seneca Jones Timber Co. - 3/2001 - M 136-60 & C.S. File 65/36-17 A-L

-----  
Found - 1"x1" Haines T iron  
74" D.Fir bears S.4 3/4°W., 136.8' healed face.  
52" D.Fir bears N.48¼°W., 47.7' bark scribed  
New BTs- 22" D.Fir bears N.67¼°E., 26.5' blazed, scribed at base "X BT"  
14" D.Fir bears S.39°E., 40.7' blazed scribed at base "X BT"