

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION C.C. for Secs. 19 & 30 only (West)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by J. H. McClung, under Contract #173, dated July 20, 1872 - (DCSO records Vol. 2 Page(s) 547)

-----  
Set post for corner to secs. 19, 24, 25 and 30, from which  
Fir 7" dia., bears N.73°E., 17 lks.  
Fir 5" dia., bears S.40°W., 15 lks.  
Dogwood 3" dia., bears N.10°W., 20 lks.  
Maple 4" dia., bears S.32½°E., 31 lks.

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 584)

-----  
A post set firmly in the ground for cor. to secs. 19 & 30, R6W, mkd. T20S S19 on NE.; R6W S30 on SE.; R7W S25 on SW. faces, S24 on NW. face, with 2 notches on S. and 4 notches on N. edges, from which  
A Fir 7" dia., bears N.73°E., 17 lks. dist. mkd. T20S R6W S19 BT.  
A Fir 5" dia., bears S.40°W., 15 lks. dist. mkd. T20S R7W S25 BT.  
A Dogwood 3" dia., bears N.10°W., 20 lks. dist. mkd. T20S R7W S13 (?) BT.  
A Maple 4" dia., bears S.32½°E., 31 lks. dist. mkd. T20S R6W S30 BT.

Wilford N. Haines (Found and recorded by Milo Godfrey, Feb. 1962 - C.S. File 49/89-29 (See Haines F.B. H-3) & M21-72)

-----  
Found - Haines' "T" Iron at corner.  
Orig. 7" now 60" Fir, N.73°E., 11.2 ft. Has been previously chopped open and good scribing visible. Apparently bark scribed "T20S R6W S19 BT 363".  
18" D.Fir, S.69°E., 40.2 ft., scribed in wood, pitched over, cannot read scribing, about 4 yrs. old.  
Stump hole and Maple shoots, S.32½°E., 20.5 ft.  
No trace of original NW. and SW. BTs.

Remonumentation of corner by Peter A. Peterson, Cadastral Surveyor, under Group #350, Sept. 1972 - (DCSO records Vol. 39 Page(s) 15707)

-----  
The cor. of secs. 19 & 30 only, perpetuated and recorded by Haines in 1958, monumented with a T shaped iron rod, 36" long, firmly set 24" in the ground with a brass disc mkd. Wilford N. Haines 239 Survey Point Drain Or,  
(Cont. Next Page)

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION C.C. for Secs. 19 & 30 only (West)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

from which the remains of the original bearing trees:

A Fir 52" dia., bears N.73°E., 17 lks. dist, with fragmentary scribe marks visible on opened blaze. Remarked by Haines in 1958; T20S R6W S19 Bt 363 on bark blaze.

A decayed Maple root crown, size indeterminate, bears S.32½°E., 31 lks. dist., no marks remaining.

and a bearing tree mkd. by Haines in 1958:

A Fir 19" dia., bears S.68°E., 61 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 20 S  
R 7 W R 6 W  
S 24 | S 19  
          | S 30  
          1972

from which a new bearing tree:

A Fir 18" dia., bears N.35°E., 54 lks. dist. mkd. T20S R6W S19 BT.

Deposit the iron rod alongside the iron post.

Fd. Haines T Iron and 1972 BLM brass cap, June 1991 by D. Peel M 113-45

Rob Ward - For: Roseburg Resources Co. & Seneca Jones Timber Co. - 3/2001 - M 136-59 & C.S. File 65/36-16B

Found - 3¼" BLM brass cap dated 1972 with Haines T iron alongside.

30" D.Fir bears N.34 3/4°E., 38.5' healed face.

28" D.Fir bears S.69°E., 39.9' healed face.

52" D.Fir stump with metal cap bears N.81½°E., 11.5' rotted face.

New BT - 17" D.Fir bears N.66°W., 13.2' blazed, scribed at base "X BT"

Steel post adjacent to corner. All BTs have red painted bands & faces plus yellow BT tag.