

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 100337

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only, T20-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 584)

Set post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on W. face; from which
A Fir 5" dia., bears N.39°E., 27 lks. dist. mkd. ¼ S BT.
A Chinquapin 6" dia., bears S.53°W., 48 lks. dist. mkd. ¼ S BT.

Looked for, not found - C.S. File 49/89-13, 2/5/1962, DCSO Milo Godfrey

Rob Ward - For: Roseburg Resources Co. & Seneca Jones Timber Co. - 3/2001 - M 136-59

Set - 5/8"x30" rebar with 2½" alum. cap mkd:
LS 1091
T20S
R7W R6W
¼ S24|
2001
10" Alder bears S.23°W. 13.3' barked scribed "¼ S24 BT"
8" Alder bears S.29°W. 21.3' barked scribed "¼ S24 BT"
14" D.Fir bears N.73°E. 23.1' blazed, scribed at base "X BT"
16" D.Fir bears S.64°E., 17.8' blazed, scribed at base "X BT"