

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24 only, T20-7

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 585)

Set post 5 ft. long, 4" sq., 24" in the ground for cor. to secs.13 & 24, mkd. T20S R7W on W.; S13 on N.; S24 on S. faces, with 3 notches on N. and S. faces, from which
A Cedar 5" dia. bears N.8°W., 12 lks. mkd. T20S R7W S13 BT
A Chittem 7" dia., bears S.44°W., 25 lks. dist. mkd. T20S R7W S24 BT.
A Cedar 4" dia., bears N.50°E., 15 lks. dist. mkd. T20S R7W S13 and 24 BT.

BLM Resurvey by Harvey E. Wofford and Lester E. Fischer, Cadastral Surveyors, under Group #913, Surveyed Aug. 1976/Aug. 1978 - (DCSO records Vol. 40 Page(s) 16068-69)

True point for the cor. of secs. 13 & 24 only, on the E. bdy. of T20S R7W.
Set an iron post 28" long, 2½" dia., 24" in the ground with brass cap mkd.
T 20 S T 20 S
S 13 R 6 W
S 24 S 19
R 7 W
1978

from which
A twin Maple 9" dia., bears N.32°W., 59 lks. dist. mkd. T20S R7W S13 BT.
An Alder 8" dia., bears S.49¼°W., 33 lks. dist. mkd. T20S R7W S24 BT.
Set a 5 ft. steel fence post alongside iron post.

From this point, the original cor. of secs. 13 & 24, bears East, 0.040 chs. dist., perpetuated and recorded by John D. Venator LS #278 in 1954, and further perpetuated and recorded by Wayne R. Tinglum, Engineering Technician for the BLM in 1976, monumented with an iron rod, ¾" dia., firmly set, projecting 6" above ground, from which the remains of a bearing tree mkd. by Todd:

A Cedar stump 20" dia., bears N.61°W., 12 lks. dist., with scribe marks BT visible on decayed blaze. (Rec, N.8°W.) and bearing trees mkd. by Tinglum:
An Alder 8" dia., bears N.74°W., 31 lks. dist., with scribe marks T20S R7W S13 BT visible on bark.
An Alder 7" dia., bears S.17½°W., 28 lks. dist., with scribe marks T20S R7W S24 BT visible on bark.
Bury iron rod at original corner position.

continued next page

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 100377

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24 only, T20-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Rob Ward - 3/2001 - C.S. File 65/36-23

Found - 3¼" BLM brass cap properly mkd.
 3/4" rebar bears S.76°10'W., 2.82'
 12" Alder bears S.50¼°W., 21.6', open face.
 14" Twin Maple N.33°W., 38.5' healed face.
New - 12" Maple bears N.8½°E., 8.0' blazed, scribed at
 base "X BT"
 Steel post adjacent to corner. All BTs have red
 painted bands & faces plus yellow BT tag.