

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19 only, (West)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by J. H. McClung, under Contract #173, dated July 20, 1872 - (DCSO records Vol. 2 Page(s) 548)

-----  
Set post for corner to secs. 18, 19, 13 & 24, from which  
A Fir 30" dia., bears S.80°E., 24 lks. dist.  
A Fir 48" dia., bears N.5°W., 50 lks. dist.  
A Maple 4" dia., bears S.45°W., 40 lks. dist.  
A Maple 3" dia., bears N.18°E., 36 lks. dist.

GL0 Survey by Thos. Todd, under Contract #574, dated May 19, 1891 - (DCSO records Vol. 2 Page(s) 585)

-----  
The cor. to secs. 18 & 19, where I find post and part of witness trees decayed. I reestablish this cor. by setting a new post, 4 ft. long, 4" sq., 24" in the ground where the old post was standing, mkd. T20S R6W on E.; S18 on N.; S19 on S. faces, with 3 notches on N. and S. faces, and mark the following witness trees:

A Fir 40" dia., bears N.5°E., 60 lks. dist. mkd. T20S R6W S18 BT.  
A Fir 48" dia., bears S.82°W., 35 lks. dist. mkd. T20S R6W S18 & 19 BT.  
A Hemlock 28" dia., bears S.63°E., 35 lks. dist. mkd. T20S R6W S19 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; C. Putnam, crew - Jan. 1962 - C.S. 49/89-9 (See 5/1958 visit C.S. 49/97)

-----  
Found - Fir tree, 84", S.82°W., 23.1 ft. has been opened previously, good scribing "S18" visible on old face. (Todd's tree)

Fir snag, dead several years, N.5°W., 36.0 ft. (instead of 33.0 ft.) Bark all gone. Found scribing "S1" on old face, looks like Todd's scribing. I believe this is McClung's tree, but scribing put on by Todd later.

No other BTs found, location in logged over area.

Set Brass cap at cor. mkd: County Surveyors Office

T 20 S  
| S 18  
| S 19  
R7W | R6W  
1962

New BTs- 16" Hemlock S.76°E. 104.0 ft mkd T20S R6W S19 DCS BT  
8" Hemlock N.40°E., 123.5 ft. "T20S R6W S18 DCS BT."

(Cont. Next Page)

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19 only, (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Resurvey by Harvey E. Wofford and Lester E. Fischer, Cadastral Surveyors, under Group #913, Surveyed Aug. 1976/Aug. 1978 - (DCSO records Vol. 40 Page(s) 16069-70)

-----  
The cor. of secs. 18 & 19 only, perpetuated and recorded by Godfrey in 1962, monumented with an iron post, 1½" dia., firmly set, projecting 10" above ground, with brass cap mkd. in 1962,

from which the remains of bearing trees mkd. by Todd:

A Fir snag, 56" dia., bears N.5°E., 60 lks. dist., no marks visible on decayed blaze.

A root hole bears S.63°E., 35 lks. dist., with a down and decayed Hemlock alongside, size indeterminate, no marks visible.

A Fir 68" dia., bears S.82°W., 35 lks. dist., with scribe marks T20S R6W visible on open blaze.

and the remains of bearing trees mkd. by Godfrey:

A Hemlock 15" dia., bears N.40°E., 187 lks. dist., with helaed blaze.

A Hemlock snag, 16" dia., bears S.76°E., 156 lks. dist., with scribe marks R6W S19 RCS BT visible on open blaze.

and bearing trees mkd. by Wayne R. Tinglum, Engineering Technician for BLM in 1976:

A Fir 5" dia., bears N.0½°E., 18 lks. dist., with scribe marks T20S R6W S18 BT.

A Fir 5" dia., bears S.32 3/4°E., 14½ lks. dist., with scribe marks T20S R6W S19 BT visible on open blaze.

Set a 5 ft. steel fence post alongside the iron post.