

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 151100

PRIMARY CORNER DESCRIPTION No. 1/4 cor. for Sec. 6 only, T21-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Wilford N. Haines, #239 - For: Woolley Logging Co. - 1956 -
M 3-23

(Not common)

Location of corner determined by proportional measurement.
Set an angle iron with brass cap at corner point, from which
84" Fir, N.07°30'E., 69.5 ft.
54" Fir, N.12°30'W., 64.0 ft.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor
and Robert H Browning, Survey Tech, Under Group No. 2268,
Surveyed March/July 2009 - DCSO records Vol. 57 Pages 22621-2

The ¼ sec. cor. of sec. 6 only, T21S R6W established by
Haines, in 1956, and is accepted as the cor., monumented with
a "T" shaped iron rod, 3/4" dia., firmly set, projecting 6"
above the ground, from which the remains of bearing trees
mkd. by Haines

A sawed fir stump, 78" dia., bears N.15¾°E., 67.8 ft.,
with a healed blaze.

A sawed fir stump, 58" dia., bears N.15¼°W., 62.5 ft.,
with a healed blaze.

and a bearing tree of unknown origin

A cedar, 23" dia., bears S.86¾°E., 14.7 ft., with
fragmentary scribe marks visible on a partially healed
blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 23" in the
ground, directly over the "T" shaped iron rod, with brass cap
mkd.

T 20 S
¼ S 6
T21S R6W
2009

from which

A hemlock, 16" dia., bears N.26°W., 16.1 ft., mkd. ¼ S6 BT