

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by J.H. McClung under Contract #173 dated July 20, 1872 - (DCSO rec. Vol. 2 Page(s) 687  
-----

Set post for ¼ sec. corner; from which  
A Chinquapin, 7" dia., bears S.82°E., 4 lks.  
A Chinquapin, 8" dia., bears N.71¼°W., 11 lks.

Wilford N. Haines, #239 - For: Woolley Logging Co. - 1956 - M 3-23  
-----

Point for corner established by proportional measurement.  
Set an angle iron with brass cap at corner point, from which  
26" Fir S.60°W., 38.5 ft.  
20" Fir N.51°W., 11.9 ft.

Douglas Co. Surveyors Office - Clell Goodwin - Lenora Ladig - Jim Cook - Gary Heichel - Mel Dunlap - 1/8/1976 - C.S. 59/2-7  
-----

Found - Haines T iron firmly in the ground & 2 BTs as follows:  
26" now 30" fir blazed & healed over bears S.60°W., 38.0 ft. (call: S.60°W., 38.5 ft.)  
20" now 24" fir bark scribed "¼ S31" bears N.54°W., 11.9 ft. (call: N.51°W., 11.9 ft.)

At the corner we set  
1"x30" IP with brass cap stamped T20S R6W  
DOUGLAS CO. SURVEYOR S 31 | S 32  
1976 ¼ |  
with Haines "T" iron driven in north of the corner.  
We do not mark any trees at this time as this area is to be logged.  
Compass decl. 20° East