

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by J. H. McClung, under Contract #173, dated July 20, 1872 - (DCSO records Vol. 2 Page(s) 680)</p> <p>-----</p> <p>Set sandstone, 3x2x2 ft., on side of high stony point bearing NW. and SW., for ¼ sec. corner, from which, A Maple 7" dia., bears N.1°E., 50 lks. dist.</p>
<p>Wilford N. Haines, #239 - For: Woolley Logging Co. - 1956 - M 3-23</p> <p>-----</p> <p>(Not common) Location for corner established by proportional measurement. Set an angle iron with brass cap at corner point, from which Marked an X in bed rock, S.24°W., 3.8 ft. 60" Fir, N.32°W., 50.2 ft. mkd. ¼ S32 BT.</p>
<p>Les Roberts - For: Seneca Jones Timber Co. - Nov. 1997 - M 127-70</p> <p>-----</p> <p>FD - "T" iron set by Haines in survey M3-23 60" fir stump, N.32°W., 50.0' (No marks), 1956 BT "X" in bedrock, S.24°W., 3.8', 1956 BT Set - 6" Fir, S.47°W., 5.4' (scribed/washer/painted red) 8" Maple, N.60°W., 9.2' (scribed/washer/painted red)</p>
<p>BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol. 57 Page(s) 22619-20</p> <p>-----</p> <p>The ¼ sec. cor. of sec. 32 only, reestablished by Haines, in 1956, by proportionate measurement, perpetuated by Roberts, in 1997, and is accepted as the cor., monumented with a "T" shaped iron rod, ¾" dia., firmly set, projecting 8" above the ground, with brass disk on top, mkd. WILFORD N HAINES RLS 239 SURVEY POINT DRAIN ORE, from which the remains of accessories mkd. by Haines An X chiseled on a rock face bears S.25°W., 3.7 ft. dist. A decayed fir stump, 43" dia., bears N.32¼°W., 50.2 ft. with no marks visible. and the remains of bearing trees mkd. by Roberts A fir snag, 6" dia., bears S.43°W., 5.0 ft., with fragmentary scribe marks visible on a partially healed blaze. A double trunk maple, 9" dia., bears N.57¼°W., 8.3 ft., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>At the corner point continued next page</p>

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set a stainless steel post, 28" long, 2½" dia., 23" in the ground, with brass cap mkd.

T20S R6W
¼ S 32
T21S
2009

Deposit a magnet in a white plastic case at the base and bury the "T" shaped iron rod alongside the stainless steel post.