

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>GL0 survey by J.H. McClung under Contract #173 dated July 20, 1872 - (DCSO rec. Vol. 2 Page(s) 687 ----- Set post for ¼ sec. cor. in canyon running SE; from which A Hemlock, 12" dia., bears N.60°E., 11 lks. A Maple, 6" dia., bears S.47½°E., 35 lks.</p>
<p>Wilford N. Haines, #239 - For: Woolley Logging Co. - 1956 - M 3-23 ----- Point for corner established by proportional measurement. Set an Angle iron with brass cap at corner point, from which: 60" Fir, N.36°E., 55.3 ft. 40" Cedar, S.85°E., 22.6 ft.</p>
<p>Wilford N. Haines - Nov. 30, 1965 - C.S. File 51/309-3 ----- Found - Stump of Cedar S.85°E., gone. Stump of Fir, N.36°E., on fire, (scribe visible) Set - New "T" iron by Creek, from which 14" Maple S.45°W., 37.8 ft. 12" R.Cedar N.31°E., 168.7 ft.</p>
<p>Les Roberts - For: Seneca Jones Timber - Jan. 2000 - M 134-6 ----- Found - Haines "T" iron set in survey M3-23. "T" iron falls on south edge of 4' wide creek. Both of Haines 1956 BTs were up-rooted by logging. Set - 8" Alder, N.42°E., 16.2' (bark scribed/metal washer, stamped PLS 1039 nailed to lower blaze. Lower blaze is painted red) 12" Alder, S.55°E., 9.0' (bark scribed/metal washer, stamped PLS 1039 nailed to lower blaze. Lower blaze is painted red)</p>
<p>BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol. 57 Pages 22635-6 ----- The ¼ sec. cor. of secs. 29 & 32, reestablished by Haines, in 1956, by proportionate measurement, perpetuated by Roberts, in 2000, and is accepted as the cor., monumented with a "T" shaped iron rod, ¾" dia., firmly set, projecting 22" above the ground, from which bearing trees mkd. by Roberts An alder, 8" dia., bears N.42¼°E., 16.1 ft., with scribe marks ¼ S29 BT visible on the bark. An alder, 13" dia., bears S.53¼°E., 8.7 ft., with scribe marks ¼ S29 BT visible on the bark. cont.</p>

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

At the corner point
Cut 1 ft. off the exposed "T" shaped iron rod (iron rod now projects 5" above ground), and drive an aluminum cap, 3/4" dia., onto the "T" shaped iron rod, with top mkd.

T20S R6W

1/4 $\frac{S\ 29}{S\ 32}$

2009

Corner is located on the S. bank of a creek, 4 ft. wide, course S.45°E.