

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33 only, (South)

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>GLO survey by J. H. McClung, under Contract #173, dated July 20, 1872 - (DCSO records Vol. 2 Page(s) 680)</p> <p>-----</p> <p>Set post for cor. to secs. 4, 5, 32 and 33, on top of spur, course N. & S. There being no tree convenient, deposited stone, 9x8x5 marked with "X".</p>
<p>GLO survey by W P Wright, U.S Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol 2 Page 733)</p> <p>-----</p> <p>Secs. 32 and 33, which post I found much decayed. Renewed the same by setting a post, 6' dia., 4 ft. long, with marked stone, 12" in ground, mkd. T20S S33 on NE.; T21S S5 on SE.; R6W S32 on NW. face, with 4 notches on E. and 2 on W. edge; from which</p> <p> Laurel 4" dia., bears N.37°W., 25 lks mkd. T20S R6W S32 BT Laurel 4" dia., bears N.36°E., 35 lks mkd. T20S R6W S33 BT Laurel 6" dia., bears S.84°E., 26 lks. mkd. T21S R6W S5 BT</p>
<p>Wilford Haines, #239 - For: Woolley Logging Co - 1956 - M3-23</p> <p>-----</p> <p>Corner located by proportional measurement. Set an angle iron with brass cap at corner point, from which</p> <p> 6" Fir, N.35°W., 16.0 ft. 4" Fir, N.16°E., 13.3 ft. 6" Fir, S.55°W., 9.4 ft.</p>
<p>Fd. OK, Oct. 1994 - M 121-24 A&B</p>
<p>Les Roberts - For: Seneca Jones Timber - 11/1997 - M127-70</p> <p>-----</p> <p>FD - "T" iron set by Haines in survey M3-23. 6" Fir, snag, N.16°E., 13.3' (scribe vis), 1956 BT. 12" Fir, N.35°W., 16.0' (scar vis), 1956 BT. 12" Fir, S.55°W., 9.4' (scar vis), 1956 BT. Set - 8" Fir, N.4°E., 11.6' (scribed/washer/painted red)</p>
<p>BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol. 57 Pages 22618-9</p> <p>-----</p> <p>The cor. of secs. 32 & 33 only, reestablished by Haines, in 1956, by proportionate measurement, perpetuated by Roberts, in 1997, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4" dia., firmly set, projecting 1" above the ground (alongside of which is a copper pipe, 1/2" dia., firmly set, projecting 14 ins. above the ground, of unknown origin), with brass disk on top, mkd. (continued next pg)</p>

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 32 & 33 only, (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which the remains of bearing trees mkd. by Haines

A fir snag, 7" dia., bears N.16°E., 13.3 ft., with a healed blaze.

A fir, 15" dia., bears S.52¼°W., 8.5 ft., with a healed blaze.

A fir, 13" dia., bears N.32¾°W., 15.7 ft., with a healed blaze.

and a bearing tree mkd. by Roberts

A fir, 9" dia., bears N.4¾°E., 11.4 ft., with fragmentary scribe marks visible on a partially healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, directly over the "T" shaped iron rod and the copper pipe, with brass cap mkd.

T20S R6W

S 32 | S 33

S 5

T21S

2009

Deposit a magnet in a white plastic case at the base of the stainless steel post.