

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 32 & 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by J.H. McClung under Contract #173 dated July 20, 1872 - (DCSO rec. Vol. 2 Page(s) 685  
-----

Set post for ¼ sec. corner; from which  
A fir, 4" dia., bears N.12°E., 50 lks.  
A Fir, 5" dia., bears N.1°W., 50 lks.

Wilford N. Haines, #239 - For: Woolley Logging Co. - 1956 - M 3-23  
-----

Found old BT, N.01°W., 33 ft.  
Set an angle iron with brass cap at point for corner.

Douglas Co. Surveyors Office - Milo Godfrey - Vernon Tracy - Clete Putnam - Feb. 1962 - C.S. File 49/89-23  
-----

Found - Haines "T" iron & cap.  
Fir tree (now 28" dia.) bears N.1°W., 32.0 ft. No scar visible. Has not been cut open. Tree has "X" & cruiser marks in bark.  
Cor. not substantiated.

Les Roberts - For: Seneca Jones Timber Co. - Nov. 1997 - M 127-70  
-----

Found - "T" iron set by Haines in survey M 3-23  
50" downed fir, N.1°W., 33.0', (No marks), 1872 BT  
Set - 6" Fir, S.7°W., 11.6' (scribed, metal, washer, painted red)  
6" Fir, S.71°E., 13.5' (scribed, metal, washer, painted red)

Fd. Ok by Les Roberts, 1/2000 - M134-6

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol. 57 Page 22641  
-----

The ¼ sec. cor. of secs. 32 and 33, perpetuated by Haines, in 1956, further perpetuated by Roberts, in 1997, monumented with a "T" shaped iron rod, ¾" dia., firmly set, projecting 15" above the ground, with brass disk on top, mkd. WILFORD N HAINES RLS 239 SURVEY POINT DRAIN ORE, from which the remains of an original bearing tree

A roothole bears N.1°W., 33.0 ft., alongside of which is a decayed fir trunk, 32" dia., with axe marks visible. and bearing trees mkd. by Roberts

continued next page

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 32 & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 8" dia., bears S.73½°E., 12.7 ft., with a healed blaze.

A fir, 8" dia., bears S.6°W., 11.2 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, directly over the "T" shaped iron rod, with brass cap mkd.

T20S R6W

¼

S 32 | S 33

2009

Deposit a magnet in a white plastic case at the base of the stainless steel post.