

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by J.H. McClung under Contract #173 dated July 20, 1872 - (DCSO rec. Vol. 2 Page(s) 685

Set sandstone, 36x24x18", for cor. to secs. 28, 29, 32, & 33.

Wilford Haines - For: Wooley Logging Co. - 1956 - M 3-23

Position for cor. located by double proportional measurement.
Set an angle iron with brass cap at corner point, from which:
40" Fir, N.25°W., 74.0 ft.
48" Fir, N.27°E., 72.4 ft.
26" Fir, S.85°E., 42.5 ft.
30" Fir, S.47°13'W., 50.2 ft.

Fd. OK by Les Roberts, 1/2000 - M 134-6

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol. 57 Pages 22633-4

The cor. of secs. 28, 29, 32, & 33, reestablished by Haines, in 1956, by proportionate measurement, and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4" dia., firmly set, projecting 2" above the ground, with brass disk on top, mkd. WILFORD N HAINES RLS 239 SURVEY POINT DRAIN ORE, from which the remains of bearing trees mkd. by Haines
A sawed, decayed fir stump, 40" dia., bears N.26½°E., 71.0 ft., with no marks visible.
A fir, 39" dia., bears S.87¾°E. 42.0 ft w/no marks visible
A sawed fir stump, 46" dia., bears S.48°W., 50.2 ft., with no marks visible.
A fir, 42" dia., bears N.22¾°W., 72.6 ft., with fragmentary scribe marks visible on the bark.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the "T" shaped iron rod, with brass cap mkd.
T20S R6W
S 29|S 28
S 32|S 33
2009
from which
A fir, 22" dia., bears N.17½°E., 93.9 ft., mkd. T20S R6W S28 BT.
A hemlock, 14" dia., bears S.21°W., 28.1 ft., mkd T20S R6W S32 BT.
Deposit a magnet in a white plastic case at the base of the stainless steel post.

cont.

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ronald L Rice - For: Silver Butte Timber Co.; Seneca Jones Timber Co.; & Oxbow Timber 1 LLC - Nov. 2014 - M168-66

Found - 5/8" rebar with the following accessories:
12" D.Fir stump bears N.62°07'W., 34.9' - scribing visible.
12" D.Fir stump bears S.35°17'W., 48.9' - no marks

New - 17" D.Fir bears N.47°E., 5.7' - blazed, scribed
SW 1/16 S28 BT
17" D.Fir bears N.40°W., 21.5' - blazed, scribed
SW 1/16 S28 BT
Steel post adjacent to corner