

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by J.H. McClung under Contract #173 dated July 20, 1872 - (DCSO rec. Vol. 2 Page(s) 686  
-----

Set post for 1/4 sec. cor.; from which  
A Cedar, 9" dia., bears N.27°E., 28 lks.  
A Hemlock, 5" dia., bears N.60°W., 12 lks.

Wilford Haines - Jan. 28, 1961 - C.S. File 51/173  
-----

Set - 1"x1"x36" T. iron for 1/4 S29|S28, from which I blaze & scribed:  
10" Yew N.81°E., 29.9 ft.  
20" Yew S.16 1/2°W., 46.9 ft.  
Found no trace of orig. 1/4 corner.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol. 57 Page 22634  
-----

The 1/4 sec. cor. of secs. 28 and 29, reestablished by Haines, in 1961, by proportionate measurement, and is accepted as the cor., monumented with an angle iron, 1"x1", firmly set, projecting 15" above the ground, from which the remains of a bearing tree mkd. by Haines

A roothole bears S.16 1/2°W., 51.6 ft., alongside of which is a yew trunk, 18" dia., with no marks visible.

At the corner point

Set a stainless steel post, 28" long, 2 1/2" dia., 23" in the ground, directly over the angle iron, with brass cap mkd.

T20S R6W

1/4  
S 29|S 28  
2009

from which

A fir, 10" dia., bears N.78 1/2°E., 43.7 ft., mkd. 1/4 S28 BT.

A fir, 19" dia., bears N.50 3/4°W., 10.5 ft., mkd. 1/4 S29 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Ronald L Rice - For: Silver Butte Timber Co.; Seneca Jones Timber Co.; & Oxbow Timber 1 LLC - Nov. 2014 - M168-66  
-----

Found - BLM brass cap dated 2009 with the following accessories:

12" D.Fir bears N.78 1/2°E., 43.7' - scribing visible

19" D.Fir bears N.50 3/4°W., 10.5' - healed face

continued next page

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New -	24" D.Fir bears S.40°W., 27.9' - blazed, scribed ¼ S29 BT
	18" D.Fir bears N.4°E., 14.3' - blazed, scribed ¼ S28 BT
	Steel post adjacent to corner