

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by J.H. McClung under Contract #173 dated July 20, 1872 - (DCSO rec. Vol. 2 Page(s) 686

- 
- Set post for corner to secs. 20, 21, 28, & 29; from which
- A Chinquapin, 5" dia., bears N.67°E., 60 lks.
  - A Fir, 60" dia., bears N.20°W., 22 lks.
  - A Fir, 34" dia., bears S.61°W., 35 lks.
  - A Fir, 55" dia., bears S.51¼°E., 75 lks.

BLM dependent resurvey by Marvin J. Lytle, Cadastral Surveyor under Group #293 dated May 1950, surveyed June/Aug. 1950 - (DCSO records Vol. 27 Page(s) 11324)

- 
- The cor. of secs. 20, 21, 28, & 29, determined from the remains of the orig. BTs:
- A stump hole bears N.65°E., 60 lks. (Rec. N.67°E.)
  - A Fir, 72" dia., bears S.70°E., 75 lks, showing a charred blaze under 78 years overgrowth ( Rec. S.51¼°E.)
  - A Fir, 48" dia. bears S.68½°W., 35 lks., showing a charred blaze under 78 years overgrowth ( Rec. S.61°W.)
  - A Fir stump, badly decayed, bears N.5°W., 22 lks., (Rec. N.20°W.)

At the corner point  
 Set an iron post, 3' long, 2" dia., 30" in the ground, with brass cap marked:

T 20 S	R 6 W
<u>S 20</u>	<u>S 21</u>
S 29	S 28
1950	

- from which
- A Fir, 14" dia., bears N.56½°E., 58 lks., mkd: T20S R6W S21 BT.
  - A Fir, 10" dia., bears S.34°E., 38 lks., mkd: T20S R6W S28 BT.
  - A Fir, 6" dia., bears N.31¼°W., 28 lks., mkd: T20S R6W S29 BT.
  - A Hemlock, 12" dia., bears N.57°W., 26 lks., mkd: T20S R6W S20 BT.

Douglas Co. Surveyors Office - Milo Godfrey - Vernon Tracy - Clete Putnam - Feb. 15, 1962 - C.S. File 49/89-14

- 
- Found - Gov't brass cap set in 1950
- Fir tree S.34°E., 25.1 ft. Tree in good condition, good scar.
  - Fir tree N.56½°E., 38.2 ft. Tree dead, scribing visible.
  - Fir tree S.31¼°W., not N.31¼°W., 18.5 ft. Tree dead, scribing visible. continued next page

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Hemlock snag, dead N.57°W., 17.2 ft. scribing visible.  
Since 3 of the BTs mkd. in 1950 are now dead, I blaze & scribe 3 new trees:  
8" D.Fir S.84°W., 40.2 ft., mkd: T20S R6W S29 DCS BT  
8" D.Fir N.77°W., 7.8 ft., mkd: S20 DCS BT  
18" D.Fir N.80°E., 28.0 ft. mkd: T20S R6W S21 DCS BT

Dan Baker - For: Weyerhaeuser Co. - 3/10/1998 - C.S. File 65/20-17

-----

Found - 1950 GLO brass cap  
NE BT down and out of position.  
21" Fir, S.34°E., 25.5 ft. - closed face, 1950 GLO  
New BTs- 17" Fir, N.83°E., 14.7 ft. to "W" nail - scribed  
"T20S R6W S21 BT"  
9" Fir, S.57°W., 8.7 ft. to "W" nail - scribed  
"T20S R6W S29 BT"  
12" Fir, N.33°W., 4.8 t. to "W" nail - scribed  
"T20S R6W S20 BT"  
6 ft. Metal fence Post 1 ft. North.

BLM dependent resurvey by Daniel N. Patterson, Cadastral Surveyor under Group No. 2300, Admin File # 0701, surveyed April 2007 - (DCSO rec Vol. 56 Pg 22309 & Plat T20-6 2011)

-----

The Cor. of Secs. 20, 21, 28 & 29, monumented with an iron post, 2" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd.  
from which the remains of a BT mkd by Lytle in 1950  
A fir, 26" dia., bears S.34°E., 25.1 ft. with a healed blaze.  
and BTs mkd by Baker  
A fir, 16" dia. bears N.80½°E. 15.1 ft with a healed blaze  
A fir, 12" dia. bears S.50¾°W., 9.5 ft with a healed blaze  
A fir, 13" dia., bears N.40¼°W., 5.3 ft. with healed blaze  
The geographic position shown hereon was determined from a direct tie to a temporary point for which a position had been determined utilizing a dual frequency, carrier phase GPS receiver, to an accuracy level of 0.20 meters or better, relative to the Nat'l Spatial Reference System, using the Nat'l Geodetic Survey On-line Positioning User Service (OPUS) Latitude 43°48'36.08"N Longitude 123°25'51.05"W (NAD 1983)

continued next page

2

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol. 57 Page 22635  
-----

The cor. of secs. 20, 21, 28, and 29, perpetuated by Godfrey, in 1962, further perpetuated by Baker, in 1998, monumented with an iron post, 2" dia., firmly set, projecting 6 ins. above the ground, with brass cap (properly) mkd.

from which the remains of bearing trees mkd. by Lytle

A roothole bears N.56½°E., 38.3 ft., alongside of which is a fallen fir trunk, 9" dia., with no marks visible.

A fir, 26" dia., bears S.34°E., 25.1 ft., with a healed blaze.

and the remains of a bearing tree mkd. by Godfrey

A sawed fir stump, size indeterminate, bears N.75°W., 8.1 ft., with no marks visible.

and the bearing trees mkd. by Baker

A fir, 15" dia., bears N.79¼°E., 15.0 ft., with a healed double blaze.

A fir, 13" dia., bears S.49½°W., 9.0 ft., with a healed double blaze.

A fir, 13" dia., bears N.40°W., 5.3 ft., with a healed double blaze.

Ronald L Rice - For: Silver Butte Timber Co.; Seneca Jones Timber Co.; & Oxbow Timber 1 LLC - Nov. 2014 - M168-66  
-----

Found - DCSO brass cap dated 1950 with the following accessories:

- 29" D.Fir bears S.34°E., 25.1' - healed face
- 18" D.Fir bears N.80½°E., 15.1' - healed face
- 15" D.Fir bears S.50¾°W., 9.5' - healed face
- 14" D.Fir bears N.40¼°W., 5.3' - healed face
- Steel post adjacent to corner