

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 308100

PRIMARY CORNER DESCRIPTION C C for Secs. 4 & 5 only, T21-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 733-34)

For closing cor. to secs. 4 & 5, I set a post, 6" dia., 4 ft. long, 12" in ground, with marked stone mkd. T20S S33 on NE.; R6W S4 on SE.; S5 CC on SW. face, with 4 notches on E. and 2 on W. edges; from which
Fir 12" dia., bears S.76°E., 79 lks. dist., mkd. T21S R6W S4 CC BT.
Fir 12" dia., bears N.23°W., 58 lks. dist. mkd. T20S R6W S33 BT.
Alder 12" dia., bears S.26°W., 69 lks. dist. mkd. T21S R6W S5 BT.

Wilford N. Haines, #239 - For: Woolley Logging Co. - 1956 - M 3-23

Location of corner established by proportional measurement. Set an angle iron with brass cap at corner point, from which
12" Fir, S.02°E., 103.3 ft.
18" Fir, S.80°W., 15.3 ft.

Fd. OK, April 1987 by D. Marx - M 105-45

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Feb. 19, 1988 - C.S. File 62/50-1

Found - No evidence of original monument found.
A 3/4" "T" iron with a 1" brass washer attached to top is firmly set and protrudes approx. 2" above ground.
No evidence found of original bearing trees.
12" Fir now 23" DBH D.Fir with a fully healed single blaze, bears S.04 3/4°E., 103.3 ft. (Rec. S.02°E., 103.3 ft.)
18" now 29" DBH D.Fir with a fully healed single blaze, bears S.80°W., 15.3 ft. as per record.
We perpetuate corner position established in Haines survey by adding a new bearing tree as follows:
A 5" DBH D.Fir scribed "X BT" bears, S.77°E., 8.5 ft
Mon is on wide low bench near foot of steep easterly slope.

Fd. OK, Oct. 1994 - M 121-24 A&B - Mon. is S.0°10'04"E., 0.31' from the true intersection point.

continued next page

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 308100

PRIMARY CORNER DESCRIPTION C C for Secs. 4 & 5 only, T21-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol. 57 Pages 22617-8

The closing cor. of secs. 4 and 5, T21S R6W reestablished by Haines, in 1956, by proportionate measurement and is accepted as the cor., monumented with a "T" shaped iron rod, 3/4" dia., firmly set, buried 2" below the surface of the ground (alongside of which is a copper pipe, 3/4" dia., loosely set, projecting 8" above the ground, of unknown origin), with brass disk on top, mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which the remains of BTs mkd. by Haines

A sawed fir stump, 27" dia., bears S.3¼°E., 103.0 ft., with a healed blaze.

A fir, 35" dia., bears S.79¾°W., 15.2 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the "T" shaped iron rod and the copper pipe, with brass cap mkd.

T 20 S
S 33
S 5 | S 4
C | C
T 21 S R 6 W
2009

from which

A fir, 25" dia., bears S.4¾°W., 63.3 ft., mkd. T21S R6W S4 CC BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.