

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 33

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Wilford N. Haines, #239 - For: Woolley Logging Co. - 10/1966  
- M 32-34

-----  
Set - 1/2" steel rod.  
Scribed - 24" Fir S.50°E., 18.0 ft.  
          24" Fir N.31°E., 12.5 ft.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor  
and Robert H Browning, Survey Tech, Under Group No. 2268,  
Surveyed March/July 2009 - DCSO records Vol. 57 Page 22638

-----  
The center 1/4 sec. cor. of sec. 33, established by Haines, in  
1966, and is accepted as the cor., monumented with a rebar,  
1/2" dia., firmly set, projecting 10" above the ground, from  
which the remains of bearing trees mkd. by Haines

    A sawed fir stump, 29" dia., bears N.34°E., 12.4 ft., with  
    no marks visible.

    A roothole bears S.50°E., 17.3 ft., alongside of which is  
    a fallen, decayed fir trunk, 32" dia., with no marks  
    visible.

At the corner point

Set a stainless steel post, 28" long, 2 1/2" dia., 21" in the  
ground, directly over the rebar, with brass cap mkd.

T20S R6W  
C 1/4 S 33  
2009

from which

    A hemlock, 7" dia., bears S.11 1/2°W., 9.7 ft. mkd. C 1/4 S33 BT

    A fir, 7" dia., bears N.83°W., 28.8 ft., mkd. C 1/4 S33 BT.

Deposit a magnet in a white plastic case at the base of the  
stainless steel post.