

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by J.H. McClung under Contract #173 dated July 20, 1872 - (DCSO rec. Vol. 2 Page(s) 686

Set post for ¼ sec. cor.; from which
 A Laurel, 8" dia., bears N.18°W., 16 lks.
 A Chinquapin, 6" dia., bears S.36°E., 10 lks.

Chas. C. Hayden, Surveyor - Fred Prella, Witness - June 1950
- C.S. File 40/255

Found - Post
 Fir 24" bears N.27°30'E., 52.0 ft. Blaze had been opened several years ago but shows no marks.
 Fir 24" bears S.73°W., 37.3 ft. Did not open.
 Found no trace of the orig. BT a Laurel 8".
Note - Fred Prella took us to this corner & said he was present when it was restored in 1936 in survey for White.

Wilford Haines - For: Wooley Logging Co. - 1956 - M 3-23

Set corner by proportional measurement.
Set angle iron with brass cap at corner point, from which
 30" fir bears North 6.9 ft.
 30" fir S.10°E., 24.0 ft.

Fd. Ok by Wilford Haines 1966, M32-34
Fd. Ok by Burt Holt May 1978, M70-14

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol. 57 Pages 22632-3

The ¼ sec. cor. of secs. 28 & 33, reestablished by Haines, in 1956, by proportionate measurement and is accepted as the cor., monumented with a "T" shaped iron rod, ¾" dia., firmly set, projecting 2" above the ground, with brass disk on top, mkd. WILFORD N HAINES RLS 239 SURVEY POINT DRAIN ORE, from which the remains of bearing trees mkd. by Haines
 A sawed fir stump, 38" dia., bears N.0¼°E., 6.4 ft., with a healed blaze.
 A fir, 49" dia., bears S.9¼°E., 23.3 ft., with a healed blaze.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, directly over the "T" shaped iron rod, with brass cap mkd.

continued next page

1

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

T20S R6W
¼ $\frac{S\ 28}{S\ 33}$
2009

from which
A fir, 7" dia., bears N.19½°E., 39.0 ft., mkd. ¼ S28 BT.
Deposit a magnet in a white plastic case at the base of the
stainless steel post.

Ronald L Rice - For: Silver Butte Timber Co.; Seneca Jones
Timber Co.; & Oxbow Timber 1 LLC - Nov. 2014 - M168-66

Found - BLM brass cap dated 2009 with the following
accessories:
39" D.Fir stump bears N.0¼°E., 6.4' - healed face
49" D.Fir bears S.9¼°E., 23.3' - healed face
7" D.Fir bears N.19½°E. 39.0' - healed face
Aluminum post adjacent to corner.