

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by J.H. McClung under Contract #173 dated July 20, 1872 - (DCSO rec. Vol. 2 Page(s) 684

Set post for ¼ sec. corner; from which
 A Fir, 5" dia., bears N.52°W., 40 lks.
 A Fir, 5" dia., bears S.37½°E., 30 lks.

Douglas Co. Surveyors Office - Ben B. Irving, Co. Surveyor - Jim Byron, Deputy Surveyor - Ray Irving & John Fee, Chainmen - For: Clarence C. Backus - April 26-29, 1954 - C.S. File 45/275 (see also C.S. File 41/274)

Found - 20" R.Fir - S.37°30'E., 19.8 scribed S ¼.
 OBT - N.52°W., 26.4 - blazed - not cut out.
Set - 1" iron pipe with brass cap mkd: County Surveyors Office ¼S 33/34 T20S R6W
Blazed & scribed:
 A 10" R.Fir, S.29°29'E., 29.8, ¼S 34 CS BT.
 A 14" R.Fir, N.78°55'W., 53.2, ¼S 33 CS BT.

Fd. 11/1983 Lloyd Smith M95-49
Fd. BC 6/1999 David Edwards M131-70

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol. 57 Pages 22627-8

The ¼ sec. cor. of secs. 33 and 34, remonumented by Irving, in 1954, monumented with an iron post, 1¼" dia., firmly set, projecting 8" above the ground, with brass cap (properly) mkd from which the remaining original bearing tree
 A fir, 31" dia., bears S.37½°E., 19.8 ft., with a hollow blaze, with no marks visible.
and the remains of a bearing tree mkd. by Irving
 A sawed fir stump, 40" dia., bears N.74°W., 51.2 ft., with no marks visible.
and new bearing tree
 A fir, 5" dia., bears S.40°W., 13.5 ft., mkd. ¼ S33 BT.
From this cor., a point established by David A. Edwards, in 1999, bears S.0°16'53"W., 94.28 ft., monumented with an iron rod, 5/8" dia., firmly set, projecting 5" above the ground, with yellow plastic cap mkd. DA EDWARD LS 2939, and is not utilized in the course of this survey.
From this same cor., a point established by person(s) unknown, bears S.3°34'09"W., 87.34 ft., monumented with an iron pipe, 2½" dia., loosely set, projecting 24" above the ground, and is not utilized in the course of this survey.