

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol 57 Pages 22629-30

The cor. of secs. 27, 28, 33, and 34, perpetuated by Hayden, in 1950, further perpetuated by Haines, in 1956, further perpetuated by Godfrey, in 1962, monumented with an iron post, 1¼" dia., firmly set, projecting 11" above the ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees
A decayed fir snag, 20" dia., bears S.76°E., 13.9 ft., with no marks visible.

A decayed fir snag, 25" dia., bears S.72°W., 15.9 ft., with no marks visible. (Record, 13.2 ft.)

and the remains of a bearing tree mkd. by Hayden

A decayed fir stump, size indeterminate, bears S.1¾°W., 17.9 ft., with no marks visible.

and the remains of bearing trees mkd. by Godfrey

A fir, 37" dia., bears N.3¾°E., 62.7 ft., with a healed blaze.

A sawed fir stump, 36" dia., bears S.76¾°W., 26.1 ft., with a healed blaze.

and new bearing trees

A hemlock, 26" dia., bears S.42¼°E., 31.1 ft., mkd. T20S R6W S34 BT.

A fir, 12" dia., bears N.27¼°W., 40.3 ft., mkd. T20S R6W S28 BT.

Fd. as per record by D. Edwards - 7/2017 - C.S. 65/96-11