TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 400240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by J.H. McClung under Contract #173 dated July 20, 1872 - (DCSO rec. Vol. 2 Page(s) 684

Set post for ¼ sec. cor.; from which
A Fir, 6" dia., bears S.66°W., 35 lks.
A Fir, 5" dia., bears N.10°E., 10 lks.

Douglas Co. Surveyors Office - Milo Godfrey - Feb. 1962 - C.S. File 49/89-13 & 49/89-38 2/16/1962

Reported as searched for & not found.

Wilford N. Haines - For: Max Dodd - Jan. 1973 - M 50-43

Set - 5/8" Steel rod.
8" Fir, S.55°W., 11.2 ft.
12" Fir, N.14°E., 15.3 ft.

Ronald L Rice - For: Silver Butte Timber Co.; Seneca Jones Timber Co.; & Oxbow Timber 1 LLC - Nov. 2014 - M168-66

Found - 5/8" rebar with the following accessories:
10" D.Fir bears S.35°W., 11.2' - healed face
12" D.Fir bears N.18°E., 15.3' - healed face
Steel post adjacent to corner

Fd. as per record by D. Edwards - 7/2017 - C.S. 65/96-11