

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 407100

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4 only, T21-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 725-26)

I set closing cor. to secs. 3 and 4 by setting post, 6" dia., 4 ft. long, with marked stone 12" in ground, marked T20S S34 on NE.; R6W CC S3 on SE.; T21S CC S4 on SW. face, with 3 notches on E. & W. edges; from which
Alder 16" dia., bears N.54°W., 29 lks. dist. mkd. T20S R6W S34 BT.
Alder 20" dia., bears S.57°E., 18 lks. dist. mkd. T21S R6W CC S3 BT.
Fir 24" dia., bears S.22°W., 83 lks. dist. mkd. T21S R6W CC S4 BT.

Wilford N. Haines, #239 - For: Woolley Logging Co. - 1956 - M 3-23

Found Fir BT to South (stump).
Set an angle iron with brass cap at corner point.
Scribed one tree:
36" Fir S.57°E., 14.7 ft. mkd. T21S R6W S3 CC BT.

Fd. OK, Nov. 1983 by Lloyd Smith - M 95-49

BLM Resurvey by Wayne L. Rogers, Cadastral Surveyor, under Group #1231, Surveyed Sept. 1984/May 1985 - (DCSO records Vol. 47 Page(s) 18061-62)

True point for the closing cor. of secs. 3 and 4.
Set an iron post 30" long, 2½" dia., with magnetic plastic breakaway base, 24" in the ground with brass cap marked:

T 20 S R 6 W
S 34

S 4 | S 3
C C
T 21 S R 6 W
1984

from which
A Fir 5" dia., bears S.43°E., 63 lks. dist. mkd. X BT.
A Fir 14" dia., bears S.41½°W., 58 lks. dist. mkd. T21S R6W S4 CC BT.

From this point, the original closing corner of secs. 3 and 4, bears N.0°34'W., 0.265 chs. dist., perpetuated and recorded by Haines in 1956, monumented with a "T" shaped iron post, 1" dia., firmly set flush with the ground with washer (Cont. Next Page)

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4 only, T21-6

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

marked WILFORD N HAINES 239 SURVEY POINT DRAIN OR,
from which the remains of an original bearing tree:
A decayed Fir stump 38" dia., bears S.22°W., 83 lks. dist.
with fragmentary scribe marks visible on an opened
blaze.
and a bearing tree mkd. by Haines
A Fir 49" dia., bears S.60°E., 23 lks. dist., with healed
blaze.

From this same point, the cor. of secs. 33 and 34 only, bears
N.88°56'W., 6.36 chs. dist.

Survey by Steven Ness - For: Weyerhaeuser Co. - Oct. 14, 1994
- M 121-24 A&B

CONDITION REPORT ONLY

Found - 3¼" BLM brass cap on 2¼" Iron pipe.
1" "T" iron with 1" brass washer, N.1°07'23"W.,
17.53 ft. from BLM monument. (Rec. N.0°34'W.,
0.265 chs.)
53" D.Fir N.51°16'E., 15.6 ft., healed face, face
points to the Haines monument.
6" D.Fir snag, S.43°08'E., 41.9 ft., two small
healed blazes, lower blaze has been damaged by
beaver. (Rec. S.43°E., 63 lks.)
34" D.Fir stump, S.29°17'W., 38.8 ft., face opened,
partial scribing visible, rest of face is burned.
(No record)
20" D.Fir N.37°09'W., 10.6 ft., healed face. (No
record)

Fd. OK by T. Baker, Sept. 2006 - M151-48

Ronald L. Rice, Ward NW - Seneca Jones Timber Co. - May 2010
- M 160-58

Found - 3¼" BLM brass cap dated 1984 with the following
accessories:
56" D.Fir bears N.51°16'E., 15.6' - healed face.
28" D.Fir bears S.40°26'W., 31.0' - healed face.
15" D.Fir bears N.37°09'W., 10.6' - healed face.
6" D.Fir bears S.16°E., 24.6' - healed face.
21" Rotted D.Fir stump bears S.29°17'W., 38.8' -
scribing visible.
1" Haines "T" iron with 1" brass washer bears
N.1°07'23"W., 17.53'

continued next page

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 407100

PRIMARY CORNER DESCRIPTION C C for Secs. 3 & 4 only, T21-6

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol. 57 Pages 22615-6

The closing cor. of secs. 3 & 4, T21S R6W monumented with an iron post, 2½" dia., firmly set, projecting 6" above the ground, with brass cap (properly) mkd.

from which the remaining bearing tree mkd. by Rogers

A fir, 27" dia., bears S.41½°W., 38.3 ft., with a healed blaze.

and new bearing tree

A fir, 6" dia., bears S.16°E., 24.6 ft., mkd. X BT.

From this cor., the original closing cor. of secs. 3 and 4, T21S R6W perpetuated by Haines, Oregon in 1956, bears N.0°34'00"W., 17.49 ft., monumented with a "T" shaped iron rod, ¾" dia., firmly set, flush with the ground, with brass disk on top, mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which the remains of an original bearing tree

A sawed fir stump, 30" dia., bears S.22°W., 54.8 ft., with no marks visible.

and a bearing tree mkd. by Haines, reported by Rogers

A fir, 56" dia., bears S.60°E., 15.2 ft., with a healed blaze.