

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 34 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by J. H. McClung, under Contract #173, dated July 20, 1872 - (DCSO records Vol. 2 Page(s) 679)

Set ¼ sec. post, from which
A Hemlock 10" dia., bears N.61°E., 20 lks.
A Dogwood 6" dia., bears S.47°W., 50 lks.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - 1961-1962 - C.S. File 49/89-40 - added 7/11/2017

Corner not found.

Survey by Lloyd D. Smith For: Oregon State Dept. of Forestry Nov. 3, 1983 - M 95-49

Set 1½" x 36" alum. pipe with 3 ¾" alum. cap with magnetic insert mkd. "Oregon State Board of Forestry", set 30" in ground., from which
10" Hemlock N.42°W., 24.5 ft. with yellow metal location poster.
34" Fir N.77°W., 46.2 ft.
4" x 4" x 72" white painted Cedar post, N.36°E., 1.8 ft.
Corner falls in center of old road, course N.73°E., from S.24°W.

BLM Resurvey by Wayne L. Rogers, Cadastral Surveyor, under Group #1231, Surveyed Sept. 1984/May 1985 - (DCSO records Vol. 47 Page(s) 18055)

The ¼ sec. cor. sec. 34 only, reestablished by proportionate measurement and recorded by Smith in 1983, there is no remaining evidence of the original corner, therefore, this position is accepted as the corner, monumented with an iron post, 2" dia., firmly set, projecting 2" above ground with brass cap mkd:

State Of Oregon
Dept. of Forestry
T 20 S R 6 W
 ¼ S 34
 1983
 LS 1101

from which bearing trees mkd. by Smith:
A Fir 35" dia., bears N.79°W., 71 lks. dist., with scribe marks ¼ S34 BT visible on open blaze.
A Hemlock 10" dia., bears N.43°W., 37½ lks. dist., with scribe marks ¼ S34 BT visible on open blaze.

Fd. Ok by David Edwards - M 130-31 - 9/1998