

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 27

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by J.H. McClung under Contract #173 dated July 20, 1872 - (DCSO rec. Vol. 2 Page(s) 685

 Set post for 1/4 sec. cor.; from which
 A Cedar, 30" dia., bears N.85°E., 21 lks.
 A Cedar, 14" dia., bears S.8°E., 6 lks.
 Brook 10 lks. N of corner, course West.

BLM dependent resurvey by Marvin J. Lytle, Cadastral Surveyor under Group #293 dated May 1950, surveyed June/Aug. 1950 - (DCSO records Vol. 27 Page(s) 11321-2)

 The 1/4 sec. cor. of secs. 22 & 27, determined from the orig. BTs:
 A Cedar, 40" dia., bears N.85°E., 21 lks., showing healed blaze scribed 1/4 S under 78 years growth.
 A Cedar, 40" dia., bears S.28°E., 6 lks., showing healed blaze facing corner. (Rec. S.28°W., 6 lks.)
 At the corner point
 Set an iron post, 3 ft. long, 1" dia., 30" in the ground, with brass cap marked: 1/4 $\frac{S\ 22}{S\ 27}$
 1950
 from which
 A Hemlock, 32" dia. bears N.7 1/4°W., 82 lks., mkd: 1/4 S22 BT.
 A Cedar, 40" dia., bears S.44 1/4°W., 9 lks., (the NW lobe of the orig. BT) mkd: 1/4 S27 BT.

Weyerhaeuser Co. by Wm. L. Wilt, Land agent - 7/13/1961 - C.S. file 53/1-9 See also C.S. 53/102-1

 From orig. GLO notes, 1950, found brass cap & BTs as follows:
 32" Hemlock N.7 1/4°W., 82 lks., good condition.
 40" Cedar S.44 1/4°W., 9 lks., good condition.
 Retracement notes - Plates, "W" nail on:
 44" Cedar N.56°E., 37.5 ft.
 40" Cedar S.44°W., 5.0 ft.

Dan Baker - For: Weyerhaeuser Co. - 11/2008 - M158-66

 Found - 2 1/2" BLM brass cap "1950"
 50" Cedar, S.44°W., (to face), 5.6' - closed face.
 46" Hemlock, N.7°W., 54.8' - closed face
 5 foot post alongside.

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol. 57 Page 22630

The ¼ sec. cor. of secs. 22 and 27, monumented with an iron post, 1" dia., firmly set, projecting 1" above the ground, with brass cap (properly) mkd.

from which bearing trees mkd. by Lytle

A cedar, 50" dia., bears S.44¼°W., 5.9 ft., with a healed blaze.

A hemlock, 44" dia., bears N.7¼°W., 54.1 ft., with a healed blaze.

and a bearing tree of unknown origin

A cedar, 60" dia., bears N.57¼°E., 39.0 ft., with no marks visible.

Corner is located on left bank of Beaver Creek, 5 ft. wide, course S.85°W.