

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by J.H. McClung under Contract #173 dated July 20, 1872 - (DCSO rec. Vol. 2 Page(s) 682-3)

Set post for ¼ sec. corner; from which
A Fir, 6" dia., bears N.67°E., 25 lks.
A Fir, 5" dia., bears S.53°W., 16 lks.

Douglas Co. Surveyors Office - Ben B. Irving, Co. Surveyor - Jim Byron, Deputy Surveyor - Ray Irving & John Fee, Chainmen - For: Clarence C. Backus - April 26-29, 1954 - C.S. File 45/275 (see also C.S. File 41/274)

Set by proportional measurement between the NE & SE corners of sec. 34.
Set - 1" iron pipe with brass pipe mkd. County Surveyor's Office 34/35 ¼ S T20S R6W 1954.
Blazed & scribed the following trees:
9" R.Fir, N.78°E., 62.2 ft. - ¼ S35 CS BT.
12" R.Fir, N.51°45'W., 34.7 ft. - ¼ S34 CS BT.

Fd. 11/1983 Lloyd Smith - M 95-49

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #2048, surveyed June/July 2003 - (DCSO records Vol. 55 Page(s) 21516-7)

The ¼ sec. cor. of secs. 34 and 35, reestablished by Irving, in 1954. There is no remaining evidence of the original cor.; therefore this position is accepted as the corner, monumented with an iron post, 1¼" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd. from which bearing trees mkd. by Irving
A fir, 15" dia., bears N.78¾°E., 61.8 ft., with a healed blaze.
A fir, 24" dia., bears N.52½°W., 34.9 ft., with a healed blaze.