

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by J.H. McClung under Contract #173 dated July 20, 1872 - (DCSO rec. Vol. 2 Page(s) 683

Set post for corner to secs. 26, 27, 34, & 35; from which
 A Fir stub, 40" dia., bears N.59°E., 20 lks.
 A Fir stub, 40" dia., bears N.30°W., 4 lks.
 A Fir, 6" dia., bears S.80°E., 25 lks.
 A Laurel, 4" dia., bears S.14°W., 19 lks.

Douglas Co. Surveyors Office - Ben B. Irving, Co. Surveyor - Jim Byron, Deputy Surveyor - Ray Irving & John Fee, Chainmen - For: Clarence C. Backus - April 26-29, 1954 - C.S. File 45/275 (see also C.S. File 41/274)

Found - 40 ft. Fir snag - N.59°E., 13.2 ft. scribed S26 BT.
 Slab of BT - N.30°W., 2.7 scribed S27 BT.
 Set - 1" iron pipe - brass cap mkd. County Surveyors Office 27|26/34|35 T20S R6W 1954
 Blazed & scribed the following trees:
 36" R.Fir - N.21°W., 31.5 - S27 T20S R6W CS BT
 18" R.Fir - S.21°W., 81.3 - S34 T20S R6W CS BT
 12" R.Fir - S.28°E., 43.8 - S35 T20S R6W CS BT
 24" R.Fir - N.26°E., 59.8 - S26 T20S R6W CS BT

Fd. 11/1983 Lloyd Smith - M 95-49

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #1495, surveyed Aug. 1989 - (DCSO records Vol. 50 Page(s) 18913)

The cor. of secs. 26, 27, 34, & 35, perpetuated & recorded by Irving, Deputy County Surveyor, in 1954, monumented with an iron post, 1¼" diam., firmly set, projecting 12" above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE

T	20	S	R	6	W	WM
				<u>27</u>		<u>26</u>
				34		35
				1954		

from which the remains of the original bearing trees
 A fir snag, 40" diam., bears N.59°E., 20 lks., with scribe marks S26 visible on decayed face.
 A fir snag, size indeterminate, bears N.30°W., 4 lks., no marks visible.
 and the remains of bearing trees mkd. by Irving
 A fir, 36" diam., bears N.25°E., 90 lks., with healed double blaze.
 A sawed fir stump, 23" diam., bears S. 28¾° E., 66 lks., no marks visible. continued next page

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A fir, 32" diam., bears S.19½°W., 123 lks., with healed double blaze.
A fir, 44" diam., bears N.22°W., 47 lks., with healed blaze and scribe marks BT visible on bark blaze.
and a new bearing tree
A hemlock, 11" diam., bears N.69°E., 36 lks., mkd. T20S R6W S26 BT.
The corner is located in the NW corner of a clearcut logged area
From this point, the BLM Geodetic Control Station No. EC 41004, at latitude 43°47'28.569"N. longitude 123°23'12.589"W. (NAD 1927), determined by the NAVSTAR Global Positioning System, bears S.13°53'15"E., 21.186 chs., monumented with an aluminum cap, 3" dia., firmly set flush with ground, in concrete, 3 ft. diam., top mkd. EC 41004 1989.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #2048, surveyed June/July 2003 - (DCSO records Vol. 55 Page(s) 21517-8)

The cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap (properly) mkd.
from which the remains of original bearing trees
A fir snag, size indeterminate, bears N.59°E., 13.2 ft., no marks visible.
A fir snag, size indeterminate, bears N.30°W., 2.6 ft., no marks visible.
and the remains of BTs mkd by Irving in 1954 reported by Rogers
A fir, 39" dia., bears N. 25° E., 59.4 ft., with a healed double blaze.
A tin-capped, sawed fir stump, 23" dia., bears S.28¾°E., 43.6 ft., no marks visible.
A sawed fir stump, 38" dia., bears S.19½°W., 81.2 ft., no marks visible.
A fir, 49" dia., bears N. 22° W., 31.0 ft., with a healed blaze and scribe marks BT visible on bark blaze.
and a bearing tree mkd. by Rogers
A hemlock, 15" dia., bears N.69°E., 23.8 ft., with scribe marks 6W S26 BT visible on a partially healed blaze.
and new bearing trees
A chinquapin, 7" dia., bears S. 33¾° E., 23.3 ft., mkd. T20S R6W S35 BT.
A fir, 7" dia., bears S. 62¾° W., 40.2 ft., mkd. T20S R6W S34 BT.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol. 57 Pages 22625-6

The cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 1¼" dia., firmly set, projecting 12" above the ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A fir snag, size indeterminate, bears N.59°E., 13.2 ft. with no marks visible.

A fir snag, size indeterminate, bears N.30°W., 2.6 ft., with no marks visible.

and the remains of BTs mkd. Irving, in 1954

A fir, 41" dia., bears N. 25° E., 59.4 ft., with a healed double blaze.

A tin-capped, sawed fir stump, 23" dia., bears S.28¾°E., 43.6 ft., with no marks visible.

A sawed fir stump, 42" dia., bears S.19½°W., 81.2 ft., with no marks visible.

A fir, 49" dia., bears N.22°W., 31.0 ft., with a healed blaze and scribe marks BT visible on the bark.

and a bearing tree mkd. by Rogers

A hemlock, 17" dia., bears N.69°E., 23.8 ft., with a healed blaze.

and remains of bearing trees mkd. by Skeesick

A chinquapin, 7" dia., bears S.33¾°E., 23.3 ft., with fragmentary scribe marks visible on a partially healed blaze.

A fir snag, 9" dia., bears S.62¾°W., 40.2 ft., with a healed blaze.

There are no suitable trees to the SW.

(NAD 1983 (CORS)) - (Page 22615)

Latitude: 43°47'41.40"N Longitude: 123°23'21.49"W