TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by J.H. McClung under Contract #173 dated July 20, 1872 - (DCSO rec. Vol. 2 Page(s) 683

Set post for ¼ sec. cor.
A Fir, 48" dia., bears S.64°E., 25 lks.
A Laurel, 6" dia., bears S.55°W., 4 lks.

Douglas Co. Surveyors Office - Milo Godfrey - Feb. 1962 - C.S. File 49/89-38

Reported as searched for & not found.

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #1495, surveyed Aug. 1989 - (DCSO records Vol. 50 Page(s) 18914)

Point for the ¼ sec. cor. of secs. 26 & 27, at proportionate distance; there is no remaining evidence of the orig. corner. Set a stainless steel post, 28" long, 2½" diam., 22" in the ground, with brass cap mkd: T 20 S R 6 W

¼
S 27 | S 26
1989

from which
A fir, 7" diam., bears S.62°E., 14 lks., mkd. ¼ S26 BT.
A fir, 33" diam., bears S.9½°W., 20 lks., mkd. ¼ S27 BT.
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H Browning, Survey Tech, Under Group No. 2268, Surveyed March/July 2009 - DCSO records Vol. 57 Pages 22626-7

The ¼ sec. cor. of secs. 26 and 27, monumented with a stainless steel post, 2½" dia., firmly set, projecting 5 ins. above the ground, with brass cap (properly) mkd.
from which bearing trees mkd. by Rogers
A fir, 10" dia., bears S.62°E., 9.2 ft., with a healed blaze.
A fir, 37" dia., bears S.9½°W., 13.2 ft., with a healed blaze.