

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by J.H. McClung under Contract #173 dated July 20, 1872 - (DCSO rec. Vol. 2 Page(s) 683

Set post for ¼ sec. cor.; from which
A Fir stub, 40" dia., bears N.20°W., 14 lks.
A Laurel, 6" dia., bears S.8°W., 19 lks.

Douglas Co. Surveyors Office - Milo Godfrey - Vernon Tracy - Clete Putnam - Feb. 1962 - C.S. File 49/89-15

Found - Old Fir snag, 40", N.20°W., 9.2 ft. Old scribing visible "¼ S BT"
No trace found of Laurel to SW.
Set - Brass cap mkd: County Surveyors T20S R6W ¼ S 26
Office 1962 S 35
27" D.Fir N.18°E., 25.4 ft. mkd: ¼ S26 CS BT
14" D.Fir S.45°E., 12.4 ft. mkd: ¼ S35 CS BT
Note - Corner lies on West slope, approx. 150 ft. W of top of ridge.

Fd. Ok Les Roberts 4/1996 - M 123-60

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #2048, surveyed June/July 2003 - (DCSO records Vol. 55 Page(s) 21519-20)

The ¼ sec. cor. of secs. 26 and 35, perpetuated by Godfrey, in 1962,, monumented with an iron post, 1¼" dia., firmly set, projecting 7" above ground, with brass cap (properly) mkd. from which the remains of an original bearing tree
A decayed stump, size indeterminate, bears N.20°W., 9.2 ft., no marks visible.
and the bearing trees mkd. by Godfrey
A fir, 39" dia., bears N.18¾°E., 25.0 ft., with a healed blaze.
A fir, 27" dia., bears S.42¼°E., 12.9 ft., with a healed blaze.
and a bearing tree mkd. by person(s) unknown
A fir, 43" dia., bears S.83¾°W., 5.7 ft., with scribe marks S BT visible on the bark.
The geographic position (NAD 1983 (CORS 96)) of the ¼ corner of sections 26 and 35, as determined by a tie to the station "DODSON BUTTE CORS ARP", is as follows:
Latitude: 43°47'40.65"N Longitude: 123°22'44.85"W