

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by J.H. McClung under Contract #173 dated July 20, 1872 - (DCSO rec. Vol. 2 Page(s) 681  
-----

Set ¼ sec. post; from which  
A Laurel, 6" dia., bears N.65°E., 52 lks.  
A Willow, 4" dia., bears N.49°W., 7 lks.

Douglas Co. Surveyors Office - Milo Godfrey - Jan. 1962 - C.S. File 49/89-13  
-----

Reported as searched for & not found.

David C. Wellman, for Weyerhaeuser Co. July 1994 - M 120-55  
-----

Found - 3/4" Iron pipe, S.10¼°W., 3.4 ft. - origin unknown.  
6" Fir, N.2°W., 5.3 ft. to pipe - 1978 Drain Dist. BLM.

14" Fir blow down, S.31°E., 19.5 ft. to pipe - 1978 Drain Dist. BLM.

Set - 2½" Brass Cap on 3/4" x 36" iron pipe marked: "T20S R6W ¼ S35|S36 PLS 2163 1994"

New Accessories -

11" Fir, N.45½°E., 27.6 ft. scribed "¼ S36 BT"

10" Fir, S.61°E., 35.7 ft. scribed "¼ S36 BT"

11" Fir, S.33°W., 28.6 ft. scribed "¼ S35 BT"

12" Fir, N.45°W., 24.0 ft. scribed "¼ S35 BT"

6' Fence post 1 ft. north.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #2048, surveyed June/July 2003 - (DCSO records Vol. 55 Page(s) 21513-4)  
-----

The ¼ sec. cor. of secs. 35 & 36, reestablished by Wellman, in 1994. There is no remaining evidence of the original cor.; therefore this position is accepted as the cor., monumented with an iron pipe, ¾" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd.

from which the remains of the bearing trees mkd. by Wellman

A sawed fir stump, 24" dia., bears N.44¼°E., 28.1 ft., with fragmentary scribe marks visible on a partially healed double blaze.

A sawed fir stump, 11" dia., bears S.61°E., 35.8 ft., with fragmentary scribe marks visible on a partially healed double blaze.

A fir, 13" dia., bears S.31¼°W., 28.5 ft., with fragmentary scribe marks visible on a partially healed double blaze.

continued next page

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A fir, 14" dia., bears N.46°W., 23.8 ft., with fragmentary scribe marks visible on a partially healed double blaze. From the corner, a point established by person(s) unknown, bears S.10°E., 3.4 ft., monumented with an iron pipe, 3/4" dia, firmly set projecting 4 ins. from the ground. This position is not utilized during the course of this survey.