


PRIMARY CORNER DESCRIPTION 1/4 Secs. 25 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by J.H. McClung under Contract #173 dated July 20, 1872 - (DCSO rec. Vol. 2 Page(s) 682)

Set sandstone, 12x10x8", for 1/4 sec. cor.

Douglas Co. Surveyors Office - Milo Godfrey - Vernon Tracy - Clete Putnam - Feb. 1962 - C.S. File 49/89-16

Found - Rock set by McClung for 1/4 cor. mkd. thus: 

Set - Brass cap to cor. mkd: County Surveyor's Office 1962
T20S R6W 1/4 S26/S25
43" D.Fir N.85°W., 21.5 ft. mkd: 1/4 S26 CS BT.
12" Hemlock S.81 1/2°E., 63.6 ft. mkd: 1/4 S25 CS BT.

BLM dependent resurvey by William W. Glenn, Cadastral Surveyor under Group #441 dated May 1962, surveyed June/July 1962 - (DCSO records Vol. 27 Page(s) 11324A)

From the 1/4 sec. cor. of secs. 25 & 26, monumented with the orig. sandstone, 12x10x8"., firmly set, 4" in the ground mkd 1/4 on the W face, alongside of which the Douglas County Surveyor has set an iron post, 1 1/4" dia., protruding 5" above ground, firmly set with (properly mkd.) brass cap.
from which the Douglas Co. Surveyors BTs:
A Fir, 13" dia., bears S.81 1/2°E., 95 lks., mkd: 1/4 S25 BT on double blaze.
A Fir, 43" dia., bears N.86 1/2°W., 34 lks., mkd: 1/4 S26 BT.
Add marks BLM 1962 to brass cap.

Fd. Ok by Les Roberts 4/1996 M123-60

BLM dependant resurvey by Daniel N. Patterson & Craig Wanless, Cadastral Surveyors, Under group #1764 dated Jan. 1995, surveyed Jan./May 1995 - (DCSO records Vol. 52 Page(s) 19699)

Beginning at the 1/4 sec. cor. of secs. 25 & 26, monumented with the original sandstone, 12 X 10 X 8", mkd. 1/4 on W. face, alongside of which is an iron pipe, 1 1/4". diam., firmly set, projecting 5" above the ground, with brass cap mkd.

T 20 S R 6 W
1/4 S 26 | S 25
BLM 1962
1962

from which bearing trees mkd. by the Douglas County Surveyor, reported by Glenn

continued next page

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Secs. 25 & 26

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A fir, 28" diam., bears S.81½°E., 95 lks., with healed blaze.
A fir, 44" diam., bears N.86½°W., 34 lks., with healed blaze.

Harvey Christensen - For: Seneca Jones Timber Co. - Sept. 2004 - M145-63

Found - 2.5' DCSO BC .6' above grade 1962
44" D.Fir N.86°W., 21.9 ft. healed face.
9" D.Fir N.22°E. 4.0 ft. blazed & scribed "¼ S25 BT"
12" D.Fir S.39°W., 12.2 ft. blazed & scribed "¼ S26 BT"
14" D.Fir S.01°W., 38.6 ft. blazed & scribed "¼ S26 BT"
25" D.Fir S.83°E., 63.1 ft. healed face.
Set - 5.5' steel post .5 ft. West.