

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 603100

PRIMARY CORNER DESCRIPTION C.C. for Secs. 1 & 2 only, T21-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 709)

I set closing cor. to secs. 1 & 2 by setting post, 6" dia., 4 ft. long, with marked stone, 12" in ground, marked T20S S36 on NE.; R6W S1 CC on SE.; S2 CC on SW. face, with 5 notches on W. and 1 on E. edge; from which
Fir 10" dia., bears N.59°W., 15 lks. dist. mkd. T20S R6W S36 BT.
Fir 10" dia., bears S.80°W., 24 lks. dist. mkd. T21S R6W S2 CC BT.
Fir 8" dia., bears S.86°E., 75 lks. dist. mkd. T21S R6W S1 CC BT.

Douglas Co. Surveyors Office - James Byron, Deputy - and crew July 31, 1958 - C.S. File 49/89-1

Found two original BTs:
10" now 36" stump, shows good scar & part of old face, N.59°W., 9.9 ft.
10" now 26" Fir, previously opened, shows good scribing "S2 BT", S.80°W., 15.8 ft.
Also find 1" angle iron set by Haines with 1" disk on top stamped "Survey point 239 Haines"
Set Brass cap at cor. mkd: County Surveyors Office
T20S R6W S36
T21S S 2 | S 1
1958
New BTs- 16" R.Fir bears N.16½°W., 27.9 ft. scribed S36 T20S R6W CS BT.
26" R.Fir bears S.80°W., 15.8 ft. scribed CC S2 T21S R6W CS BT.
30" R.Fir bears East, 9.0 ft. scribed CC S1 T21S R6W CS BT.

BLM Resurvey by Norman J. McDonald, Survey Technician, under Group #469, Surveyed May/June 1962 - (DCSO records Vol. 31 Page(s) 13095-96)

(81.58 chs.)
Point for the closing cor. of secs. 1 and 2, at intersection with the S. bdy. of sec. 36, T20S R6W.
Set an iron post 30" long, 2½" dia., 26" in the ground, with brass cap mkd.
(Cont. Next Page)

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 603100

PRIMARY CORNER DESCRIPTION C C for Secs. 1 & 2 only, T21-6

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

T20S
S 36
S 2 | S 1
C C
T 21 S R 6 W
1962

from which
A Fir 35" dia., bears S.77°E., 125 lks. dist. mkd. T21S R6W S1 CC BT.
A Fir 25" dia., bears S.74°W., 115 lks. dist. mkd. T21S R6W S2 CC BT.

From this point, the original closing cor. of secs. 1 and 2, bears N.0°02'E., 0.12 chs. dist., perpetuated with a DCSO survey marker, an iron post 1" dia., protruding 8" from the ground, firmly set, with brass cap mkd. in 1958., from which the remaining original bearing trees:
A sawed Fir stump 30" dia., bears N.52½°W., 15 lks. dist., with axe marks visible on old face. (Rec. brg. N.59°W.)
A Fir 24" dia., bears S.80°W., 24 lks. dist. mkd. S2 T21S R6W BT.

Trees mkd. by the County:
A Fir 18" dia., bears N.16½°E., 42 lks. dist., with illegible scribe marks visible on partially healed blaze.
A Fir 32" dia., bears E., 14 lks. dist. mkd. T21S R6W CC S1 CS BT.
A Fir 24" dia., bears S.80°W., 24 lks. dist. mkd. CC S2 T21S R6W CS BT. (Remarked original bearing tree)

I add marks AM to the original bearing trees.

Fd. OK by 12/92, L.Roberts M 116-43 & C.S. 63/149-3D
Fd. BC & 5 BTs by Corey Woodruff, 4/2013 - M165-16

2