

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by J.H. McClung under Contract #173 dated July 20, 1872 - (DCSO rec. Vol. 2 Page(s) 682

Set ¼ sec. post; from which
 An Alder, 6" dia., bears S.81°W., 20 lks.
 An Alder, 5" dia., bears S.59°E., 21 lks.

Douglas Co. Surveyors Office - Milo Godfrey - Jan. 1962 - C.S. File 49/89-13

Reported as searched for & not found.

BLM dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #1839 surveyed May 1997 - (DCSO recs. Vol. 53 Pg(s) 20370)

Point for the ¼ sec. cor. of secs. 25 & 36, at proportionate diastance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2½" diam., 26" in the ground, with brass cap mkd. T 20 S R 6 W

1/4 $\frac{S\ 25}{S\ 36}$
1997

from which

 A fir, 14" diam., bears N.62°E., 17½ lks. mkd. 1/4 S25 BT.

 A fir, 21" diam. bears S. 43¾° E. 22½ lks. mkd. 1/4 S36 BT

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this point, a point established by person(s) unknown, bears N. 3° 09' 35" E., 0.024 chs. dist., monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 8 ins. above the ground, from which a bearing tree mkd. by person(s) unknown,

 A fir, 55" dia., bears N.11¼°W., 71½ lks., with no mks. visible.