

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 (SE Tsp. Cor.)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Harvey Gordon, Deputy Surveyor, Under Contract #49, dated Oct. 17, 1854 - (DCSO records Vol. 2 Page(s) 678)

-----  
Set post corner of Townships 20 and 21 South of Ranges 5 and 6 West, from which

- A R.Fir 20" dia., bears N.87°W., 120 lks. dist.
- A R.Fir 20" dia., bears S.82°W., 89 lks. dist.
- A R.Fir 15" dia., bears S.28°E., 73 lks. dist.
- A Redwood 30" dia., bears N.36°E., 105 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - June 18, 1958 - C.S. File 49/89-3

-----  
Found - Orig. 30" now 54" Cedar N.36°E., 69.3 ft., I do not open.

Orig. 20" now 40" stump, good scribing visible "S" N.87°W., 79.2 ft.

Orig. 20" now 42" stump, shows scar. I do not open, S.82°W., 58.7 ft.

Orig. SE. BT would be in roadway.

Set Brass cap at cor. mkd: County Surveyors Office 1958  
T 20 S

		Lane Co		
R6W	S 36		S 31	R5W
Doug Co	S 1		S 6	
			T 21 S	

(Corner on South edge of logging road.)

New BTs- 18" Laurel N.13°W., 105.0 ft. scribed S36 T20S R6W CS BT.

14" R.Fir S.78°E., 24.5 ft. scribed S6 T21S R5W CS BT.

19" Cedar S.75°W., 97.0 ft. scribed S1 T21S R6W CS BT.

14" R.Fir N.45°E., 32.4 ft. S31 T20S R5W CS BT.

BLM Resurvey by Norman J. McDonald, Survey Technician, under Group #469, Surveyed May/June 1962 - (DCSO records Vol. 31 Page(s) 13089-90)

-----  
The tsp. corner, which has been perpetuated with a DCSO survey marker, an iron post, 1" dia., protruding 8" from the ground, firmly set, with brass cap mkd. in 1958, from which the remaining original bearing trees:

A Cedar 52" dia., bears N.36°E., 105 lks. dist., with a healed blaze.

A sawed Fir stump 48" dia., bears S.82°W., 89 lks. dist., with bottom of healed blaze visible.

(Cont. Next Page)

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 (SE Tsp. Cor.)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A sawed Fir stump 48" dia., bears N.87°W., 120 lks. dist.,  
mkd. S on opened blaze.  
Trees mkd. by the County  
A Fir 14" dia., bears N.45°E., 49 lks. dist. mkd. S31 T20S  
R5W CS BT.  
A Fir 14" dia., bears S.78°E., 48 lks. dist. mkd. S6 T21S  
R5W CS BT.  
A Cedar 20" dia., bears S.75°W., 147 lks. dist. mkd. S1  
T21S R6W CS BT.  
A Madrone 24" dia., bears N.18°W., 159 lks. dist. mkd. S36  
T20S R6W CS BT.  
and new bearing trees:  
A Fir 16" dia., bears N.6°E., 80 lks. dist. mkd. T20S R5W  
S31 BT.  
A Fir 16" dia., bears S.59°E., 54 lks. dist. mkd. T21S R5W  
S6 BT.  
A Fir 6" dia., bears S.37°W., 151 lks. dist., mkd. T21S  
R6W S1 BT.  
A Fir 6" dia., bears N.22°W., 165 lks. dist., mkd. T20S  
R6W S36 BT.  
I stamp USBLM 1962 on brass cap.  
Corner falls at W. edge of dirt road, 15 lks. wide, bears N.  
and S.

William L. Wilt - Weyerhaeuser Co. - March 10, 1964 - C.S.  
File 53/102-7

-----  
Found Corner OK. Added "W" nails and plates to BLM 1962 BTs.

Fd. OK and used in BLM Resurvey by Floyd A. Brooks and  
Timothy A. Kent, Cadastral Surveyors, under Group #648,  
Surveyed Aug. 1967/Sept. 1971 - (DCSO records Vol. 37 Page(s)  
15266)

Douglas Co. Surveyors Office - Gregory Quibell, Deputy -  
Randy Smith; John Powell, crew - May 10, 1983 - C.S. File  
62/7-1

-----  
Found - 1958 DCSO brass cap lying on ground alongside road.  
Cap also restamped 1962 by BLM.  
Also found hole which brass cap had been pulled out of. From  
hole BTs bear:  
Orig. 30" now 52" Cedar with well healed blaze bears  
N.36°E., 69.3 ft.  
Orig. 20" now 48" sawed Fir stump with well healed  
blaze, bears S.82°W., 58.7 ft.  
(Cont. Next Page)

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 (SE Tsp. Cor.)

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Orig. 20" now 48" sawed Fir stump with no blaze visible, bears N.87°W., 78.2 ft.  
14" Fir now 18" with well healed blaze, bears N.45°E., 32.3 ft. (1958)  
14" Fir now 20" with well healed blaze, bears S.78°E., 24.5 ft. (1958)  
20" Cedar now 29" with well healed blaze, bears S.75°W., 97.0 ft. (1958)  
24" Madrone now 26" stump bears N.18°W., 104.9 ft. (1958)  
16" Fir now 26" with well healed blaze, bears N.6°E., 52.8 ft. (Resurvey)  
16" Fir, now 25" with well healed blze, bears S.59°E., 35.6 ft. (Resurvey)  
6" Fir now 16" with well healed blaze bears S.37°W., 99.7 ft. (Resurvey)  
6" Fir now 10" with well healed blaze, bears N.22°W., 108.9 ft. (Resurvey)  
Since found hole fits well, I RESET found brass cap in its original hole and add the marks 1983 to cap.

Fd. OK in BLM resurvey by Wayne L. Rogers, Cadastral Surveyor, Group #1612, surveyed June, 1991 - (DCSO records Vol. 50 Page(s) 19220)

Fd. Ok by Craig Wanless, 8/2005 - M148-38