TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 36; & 31, T20-5

Alias Description
Alias Description
Alias Description
Alias Description

GLO Survey by Harvey Gordon, Deputy Surveyor, Under Contract #49, dated Oct. 17, 1854 - (DCSO records Vol. 2 Page(s) 678)

Set ¼ sec. post, from which
A R.Fir 30" dia., bears N.61°W., 25 lks. dist.
A R.Fir 15" dia., bears N.23°E., 29 lks. dist.
A mountain peak, said to be near the right bank of Siuslaw Creek, bears N.64°57'W., 20.95 miles dist.
A 2nd peak bears N.66°21'W., 21.40 miles dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; C Putnam, crew - Jan. 1962 - C.S. File 49/89-11

Found - Fir tree, now 34", N.23°E., 19.1 ft. This tree has been opened previously and good scribing "4S" visible on old face. Tree still in good condition.
Rotted remnants of old Fir stump, N.61°W., 16.5 ft. Too far gone to find any markings.
Set Brass cap at cor. mkd: Douglas County Surveyors Office

T 20 S
1/4 S 36|S 31
R 6 W R 5 W
1962

New BTs- 15" Hemlock S.54°E., 17.6 ft. mkd. ¼ S31 DCS BT.
7" Hemlock N.63°W., 17.4 ft. mkd. ¼ S36 DCS BT.
Corner is on County line between Douglas and Lane.

Corner Fd. OK in BLM Resurvey by Brooks and Kent, under Group #648, surveyed Aug. 1967/Sept. 1971 - (DCSO records Vol. 37 Page(s) 15267)

Add the marks, BLM 1967 to the brass cap.

David Wellman, for Weyerhaeuser Co., March 3, 1997 - C.S. File 65/20-1

Found - Douglas County Brass Cap dated 1962
30" Fir stump w/tin cap, N.28°E., 20.0 ft. to spike set side center - closed face.
23" Hemlock, N.61°W., 17.4 ft. to spike set side center - closed face.
23" Hemlock, S.54°E., 17.6 ft. to spike set side center - closed face. (rec. N.54°E)
New - 26" Hemlock, S.17½°W., 32.7 ft. to "W" nail - scribed "1/4 S36 BT"