

TOWNSHIP 20 RANGE 06 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 25; & 30, T20-5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Harvey Gordon, Deputy Surveyor, Under Contract #49, dated Oct. 17, 1854 - (DCSO records Vol. 2 Page(s) 677)

Set ¼ sec. post, from which
A R.Fir 14" dia., bears N.35°W., 13 lks. dist.
A R.Fir 15" dia., bears S.62°E., 14 lks. dist.

Douglas Co. Surveyors Office - Milo Godfrey - Jan. 1962 - C.S. File 49/89-13

Reported as searched for & not found.

BLM Resurvey by Floyd Brooks and Timothy Kent, Cadastral Surveyor, under Group #648, surveyed Aug. 1967/Sept. 1971 - (DCSO records Vol. 37 Page(s) 15269)

Point for the ¼ sec. cor. of secs. 25 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 28" long, 2½" dia., 24" in the ground with brass cap mkd:
 1/4
 S 25|S 30
 T 20 S
 R 6 W R 5 W
 1967

from which
A Fir 47" dia., bears N.82°E., 105 lks. dist. mkd. ¼ S30 BT.
A Maple 13" dia., bears S.15½°W., 84 lks. dist. mkd. ¼ S25 BT.